

Spin-On® Series Fittings and Accessories


Spin-On® Series II Connectors and Accessories



CAT. NO.	HUB SIZE NPT	CABLE RANGE OVER ARMOR (IN.)	DIMENSIONS (IN.)		OPTIONAL CORROSION RESISTANT BOOT CAT. NO.
			A DIA.	B	
2-050-008	½	.380-.435	1¼	1½	NB050
2-050-010	½	.436-.500	1¼	1½	NB050
2-050-020	½	.501-.580	1¼	1½	NB050
2-050-030	½	.581-.650	1¼	1½	NB050
2-075-040	¾	.651-.730	1½	2½	NB075
2-075-050	¾	.731-.820	1½	2½	NB075
2-075-060	¾	.821-.880	1½	2½	NB075
2-100-070	1	.881-0.960	2	2½	NB100
2-100-080	1	.961-1.030	2	2½	NB100
2-100-090	1	1.031-1.100	2	2½	NB100
2-100-100	1	1.101-1.180	2	2½	NB100
2-125-110	1¼	1.181-1.240	2¼	2½	NB125
2-125-120	1¼	1.241-1.310	2¼	2½	NB125
2-125-130	1¼	1.311-1.390	2¼	2½	NB125
2-150-140	1½	1.391-1.480	2½	2½	NB150
2-150-150	1½	1.481-1.570	2½	2½	NB150
2-150-160	1½	1.571-1.660	2½	2½	NB150
2-200-170	2	1.661-1.750	3	2½	NB200
2-200-180	2	1.751-1.840	3	2½	NB200
2-200-190	2	1.841-1.930	3	2½	NB200
2-200-200	2	1.931-2.030	3	2½	NB200
2-250-210	2½	2.031-2.150	3½	3½	NB250
2-250-220	2½	2.151-2.270	3½	3½	NB250
2-250-230	2½	2.271-2.390	3½	3½	NB250
2-250-240	2½	2.391-2.510	3½	3½	NB250
2-300-250	3	2.511-2.640	4½	3½	NB300
2-300-260	3	2.641-2.770	4½	3½	NB300
2-300-270	3	2.771-2.900	4½	3½	NB300
2-300-280	3	2.901-3.040	4½	3½	NB300
2-350-300	3½	3.171-3.310	5	3½	NB350
2-350-310	3½	3.311-3.450	5	3½	NB350
2-350-320	3½	3.451-3.590	5	3½	NB350
2-400-330	4	3.591-3.730	5½	3½	NB400
2-400-340	4	3.731-3.870	5½	3½	NB400

UL File No. E38947

CSA File No. LR 2884



Connector
Aluminum



In corrosive environments, the T&B neoprene boot provides maximum corrosion protection to the connector. Simply match the connector hub size to the boot hub size to select the proper boot (NB Series).