

Non-Metallic Liquidtight Cord Connectors

Low-profile cable gland perfect for tight spots.

Non-Metallic Cable Glands

T&B Nylon Cable Glands have a sturdy cable sealing mechanism that results in superior strain relief. The compact size ensures quick and easy installation in cramped spaces. The non-metallic construction provides excellent corrosion, chemical and impact resistance. The glands have long threads and locknuts are available.



- Halogen free
- Flame-retardant UL94V-0
- UL® Listed*, CSA Certified for certain ranges of cable
- Working temperatures: -30° C (-22° F) to 80° C (176° F)
Continuous, +150° C (276° F) Intermittent
- Meets VDE ratings

* Material not UV resistant. Sturdy Nylon 6 for strong, lightweight construction. Gray color shown; also available in black.



CAT. NO. FITTINGS	TRADE SIZE	COLOR	CORD RANGE		LENGTH OF THREAD		USE T&B LOCKNUT CAT. NO.	UNIT PKG.	STD. PKG.
			IN.	MM	IN.	MM			
NPT Threads									
CC-NPT38-B	¾"	Black	.197-.394	5-10mm	.590	15mm	—	50	250
CC-NPT38-G	¾"	Gray	.197-.394	5-10mm	.590	15mm	—	50	250
CC-NPT12-B	½"	Black	.394-.551	10-14mm	.590	15mm	LN501	50	250
CC-NPT12-G	½"	Gray	.394-.551	10-14mm	.590	15mm	LN501	50	250
CC-NPT34-B	¾"	Black	.512-.709	13-18mm	.590	15mm	LN502	25	100
CC-NPT34-G	¾"	Gray	.512-.709	13-18mm	.590	15mm	LN502	25	100
CC-NPT1-B	1"	Black	.709-.984	18-25mm	.709	18mm	LN503	20	100
CC-NPT1-G	1"	Gray	.709-.984	18-25mm	.709	18mm	LN503	20	100
ISO/Metric Threads									
CC-ISO16-G	16"	Gray	.197-.394	5-10mm	.394	10mm	LN-ISO16-G	50	200
CC-ISO20-G	20"	Gray	.236-.473	6-12mm	.590	15mm	LN-ISO20-G	50	200
CC-ISO25-G	25"	Gray	.512-.709	13-18mm	.590	15mm	LN-ISO25-G	25	100
CC-ISO32-G	32"	Gray	.709-.984	16-25mm	.590	15mm	LN-ISO32-G	20	100
CC-ISO40-G	40"	Gray	.748-1.10	22-32mm	.709	18mm	LN-ISO40-G	15	75
PG Threads									
CC-PG7-G	7"	Gray	.118-.256	3-6.5mm	.315	8mm	LN-PG7-G	50	200
CC-PG9-G	9"	Gray	.157-.315	4-8mm	.315	8mm	LN-PG9-G	50	200
CC-PG11-G	11"	Gray	.197-.394	5-10mm	.315	8mm	LN-PG11-G	25	100
CC-PG135-G	13½"	Gray	.236-.473	6-12mm	.354	9mm	LN-PG135-G	25	100
CC-PG16-G	16"	Gray	.394-.551	10-14mm	.394	10mm	LN-PG16-G	25	100
CC-PG21-G	21"	Gray	.512-.709	13-18mm	.433	11mm	LN-PG21-G	10	50
CC-PG29-G	29"	Gray	.709-.984	18-25mm	.433	11mm	LN-PG29-G	10	50
CC-PG36-G	36"	Gray	.867-1.26	22-32mm	.512	13mm	LN-PG36-G	10	50

Listed under UL file E13938, control #137B. NPT and PG threaded Cable Glands are UL Listed; ISO/Metric Threaded Cable Glands are not UL Listed.