



# Accessory Products

Closure caps for receptacles, connectors and Multi-ports  
 Threaded unions for mating (2) cordsets  
 Female and male plugs for liquid tight conduit terminations  
 90° adapters with (1) male and (1) female plug

CLOSURE CAPS & THREADED UNIONS					
DESCRIPTION	FOR USE WITH	FIG	2P to 6P (A size)	6P (B size) to 8P	9P to 12P
ALUMINUM CLOSURE CAP WITH INTERNAL THREADS	MALE & FEMALE RECEPTACLES + MULTIPORT BASE UNITS	1	65-0086	65-0103	65-0105
ALUMINUM CLOSURE CAP WITH EXTERNAL THREADS	MALE & FEMALE CONNECTORS	2	65-0085	65-0102	65-0104
ALUMINUM THREADED UNION	MALE & FEMALE CONNECTORS	3	55-0426	55-0466	55-0496

MINI-CHANGE® PLUGS WITH #16 AWG PVC LEADS 6'-0" LONG FOR 1/2" LIQUID TIGHT CONDUIT					
		2P	3P	4P	5P
FEMALE FACE VIEW					
COLOR CODE		1- white 2- black	1- green-gnd 2- black 3- white	1- black 2- white 3- red 4- green-gnd	1- white 2- red 3- green-gnd 4- orange 5- black
FEMALE	FIG 4	40718	40925	41132	41344
MALE	FIG 4	40780	41037	51149	41593

90° ADAPTERS WITH (1) MALE PLUG AND (1) FEMALE PLUG					
		2P	3P	4P	5P
90°	FIG 5	40761	41048	41212	41481

# Specifications



- MECHANICAL**  
 CLOSURE CAPS W/ INTERNAL THREADS: GRAY ANODIZED ALUMINUM  
 CLOSURE CAPS W/ EXTERNAL THREADS: BLACK ANODIZED ALUMINUM  
 THREADED UNION: GRAY ANODIZED ALUMINUM  
 LIQUID-TIGHT PLUGS: ZINC PLATED STEEL  
 CONNECTOR BODY: ZINC PLATED STEEL  
 COUPLING NUT: GRAY ANODIZED ALUMINUM  
 CLAMP NUT: ZINC PLATED STEEL  
 INSERT: PVC - UL STD 94 - V0  
 90° ADAPTER CONNECTOR BODY: YELLOW NYLON  
 COUPLING NUTS: ZINC DIECAST W/ BLACK EPOXY  
 INSERT: PVC - UL STD 94 - V0
- ELECTRICAL**  
 LIQUID-TIGHT PLUGS AND 90° ADAPTORS: 600V  
 VOLTAGE RATING: CURRENT: 2P - 13A  
 3P - 10A  
 4P - 8A  
 5P - 8A
- ENVIRONMENTAL**  
 PROTECTION: IP65, NEMA 4  
 AMBIENT OPERATING TEMP: -4° TO 221° F (-20° TO 105° C)
- CERTIFICATIONS**  
 UL: UL RECOGNIZED, FILE NO. E46237  
 CSA: CSA CERTIFIED, FILE NO. LR6837

## ACCESSORY DIMENSIONS & DETAILS

