Floor Boxes

Accessories

Problem Solvers and Replacement Components Protective Ring for 2½ in. Threaded Covers

Description	Catalog Numbers
Provides mechanical and wet mop protection	S3061
for plugs and receptacles (brass).	

Theater Seating Floor Box

Description	Catalog Numbers
The theater seating floor box is nonadjustable and provides	F3185
a ¾ in. threaded hub for conduit connection to theater aisle	
lights. It permits opening of the enclosure for wiring without	
disturbing above floor connections. Other features include a	
cast iron box with a corrosion-resistant finish and a blank	
steel cover. Knockouts: (¾ in. surface, ¾ in. sides, ¾ in. bottom)	
18.80 cu. in. (380 cubic cm).	

Adjustable Tops (Brass)

Brass Outlet Fittings for Conduit Systems.

Future requirements for floor outlets may be accommodated by systematically studding the floor with these fittings, all radiating from one or more floor boxes, from which any changes or additions may be subsequently made by the pulling of wires from box to the outlet. Adjustment tops are male connections to be mounted on elbow or tee fittings. They provide a pre-pour adjustment and an available connection for above-floor service heads.

Description	Α	В	Catalog Numbers		
3/4 in. threaded conduit size (male).	1.25" (31.8)	1.44" (36.6)	F1339		
1 in. threaded conduit size (male).	1.31" (33.3)	1.75" (44.5)	F1539		
Note: Adjustment: ¾ in. and 1 in. fittings permit ½ in. vertical adjustment.					

Coupling (Brass)

Couplings are utilized for straight conduit connections when a floor box is not required. The conduit stub is brought to within approximately 1½ in. of the planned surface, and the coupling is mounted and adjusted prior to the concrete pour. Standard service heads may be mounted to the couplings as required.

Description	Α	В	Catalog Numbers
¾ in. threaded conduit size (female).	1.44" (36.6)	1.25" (31.8)	F1340

Protective Ring for 21/8" Threaded Covers




S3061

Theater Seating Floor Box



F3185

Adjustable Tops (Brass)



Coupling (Brass)



F1340