






Dimensions Inches (mm)

	Stamped Steel	Cast Iron
Style	<p>6-Gang</p>  <p>LCFBSSA</p>	<p>6-Gang</p>  <p>LCFBCA</p>
Min. Depth of Pour	3.50" (89)	3.65" (93)
Adjustability	Fully	Fully
Cubic Inch (cm ³) Capacity Per Chamber	(4) at 38.2 cu. in. (626 cm ³) (2) at 25.4 cu. in. (416 cm ³)	(4) at 36.8 cu. in. (603 cm ³) (2) at 25.4 cu. in. (416 cm ³)
Dimensions A	6.18" (157)	6.35" (161)
Dimensions B	12.95" (329)	13.11" (333)
Dimensions C	12.95" (329)	13.11" (333)
Threaded Access Holes Per Chamber	-	(1) 3/4" & (1) 1 1/4"
Knockouts Per Chamber	(1) Concentric 1", 1 1/4" & (1) 3/4"	-
Concrete Cover Included	✓	✓
Closure Plugs Included	-	✓
Cover Mounting Brackets Included*	✓	✓



Note: *Replacements Mounting Brackets available, (1 pair) **LCFBBRACKET**. UL File Number E31999. CSA File Number LR18416.

On-Grade Barrier

Intended for use on installations at grade level. Installed prior to the concrete pour and provides a barrier between the soil. The on-grade barrier comes with leveling feet and anchor points.

CFBOGPAN4



Pour Pan Dimensions:
15.75 in. sq.
4 in. depth

Floor Box Covers Recessed Floor Box Covers

Smooth metallic cover, flange and cable doors; for carpet applications	Cover Dimensions 10.30" x 10.30"	LCFBCxxTC	
Metallic cover, flange and cable doors for carpet applications, carpet insert required	Cover Dimensions 10.30" x 10.30"	LCFBCxxC	
Smooth metallic cover and cable doors for tile applications	Cover Dimensions 8.31" x 7.70"	LCFBCxxT	
Reinforced non-metallic cover, flange and cable doors; for carpet applications, carpet insert required	Cover Dimensions 10.30" x 10.30"	LCFBCxxA	

xx = Color: **AL** (Aluminum Finish), **BRS** (Brass Finish), **BK** (Black) and **GY** (Gray). ****** = Color: **BK** (Black), **BR** (Brown), **GY** (Gray) and **I** (Ivory).


Face Plates

LCFBP8



Duplex

LCFBP26



Style Line®
Decorator Opening

LCFBP720



Single Receptacle
(for 1.56" boss dia.)

LCFBIM



3-Unit Hubbell iSTATION
(See Section C for module options)

LCFBP14



Blank



Complies with UL514 A & C