



**IMPORTANT**

Read all breaking strength, safety and technical data relating to this product. Pages V-51 to V-54.



**Fiber Optic Pulling Grip, Flexible Eye, Low Profile, Double/Single Weave Mesh**

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	E Approx. Inches (cm)	M Approx. Inches (cm)	Catalog Number
.10"-.22 (.25-.56)	900 (4,003)	7.5" (19)	10" (25)	<b>033291193</b>
.21"-.35" (.53-.89)	1,400 (6,227)	7.5" (19)	14" (36)	<b>033291194</b>
.32"-.48" (.81-1.22)	2,000 (8,896)	8.5" (22)	19" (48)	<b>033291195</b>
.42"-.61" (1.07-1.55)	2,500 (11,120)	8.5" (22)	21" (53)	<b>033291196</b>
.53"-.74" (1.35-1.88)	3,000 (13,344)	8.5" (22)	23" (58)	<b>033291197</b>
.64"-.87" (1.63-2.21)	4,200 (18,682)	8.5" (22)	25" (64)	<b>033291198</b>
.75"-1.00" (1.90-2.54)	4,200 (18,682)	8.5" (22)	28" (71)	<b>033291199</b>



**Fiber Optic Slack Pulling Grip, Split Mesh Rod Closing, Single Weave**

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	E Approx. Inches (cm)	M Approx. Inches (cm)	Catalog Number
.25"-.37" (.63-.94)	300 (1,334)	3" (7.6)	4.7" (12)	<b>033291015</b>
.38"-.49" (.97-1.24)	800 (3,558)	3" (7.6)	5" (13)	<b>033291016</b>
.50"-.61" (1.27-1.55)	800 (3,558)	3" (7.6)	7.5" (19)	<b>033291017</b>
.62"-.74" (1.57-1.88)	1,200 (5,338)	3" (7.6)	8" (20)	<b>033291018</b>

Note: E-Eye length. M-Mesh length at nominal diameter.