

Fire-Rated Poke-Throughs for Concrete Floors

Flush Furniture Feed FRPT

3 Inch Core Hole Units

Large Capacity, Single-Service Flush Furniture Feed FRPT, Two-Piece Units

| Description | Catalog Number | Description | Color/Material | Catalog Number |
|---|----------------|--|--|--|
| <p>Large Capacity, Single-Service Through Floor Fitting with (1) 2 in. EMT stem. Will accommodate up to 36 Category 5e cables.</p> <p>Specifications:</p> <ul style="list-style-type: none"> • 1- to 2-hour fire rating • Single-Service, Power or Data • For 2¼ to 7 in. floor thickness • UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area • Approved for use in the City of Chicago | PT2FIT | <p>Large Capacity Cover/Flange</p> <p>Specifications:</p> <ul style="list-style-type: none"> • Cover/flange with 1¼ in. and 2 in. trade size combination knockout • Painted aluminum cover and flange • Approved for use in the City of Chicago | <p>Brass Finish</p> <p>Black</p> <p>Gray</p> | <p>FF2BRS</p> <p>FF2BK</p> <p>FF2GY</p> |



Note: *Includes pre-wired 20A isolated ground duplex Style Line® receptacle. See page P-32 for technical information.

Flush Furniture Feed FRPT, One-Piece Units

| Description | Color | Catalog Number | Description | Color | Catalog Number |
|---|---------------------------------------|---|--|---------------------------------------|--|
| <p>3-Service Furniture Feed Poke-Through</p> <p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> • PT73SD floor fitting • Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¼ in. threaded hub for power • Painted aluminum flange | <p>Black</p> <p>Gray</p> <p>Ivory</p> | <p>PT73FFSDBK</p> <p>PT73FFSDGY</p> <p>PT73FFSDI</p> | <p>Single-Service Furniture Feed Poke-Through</p> <p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> • PT71SD floor fitting • Aluminum cover with (1) KO to accept a ¼ in. connector • Painted aluminum flange | <p>Black</p> <p>Gray</p> <p>Ivory</p> | <p>PT7FFSDBK</p> <p>PT7FFSDGY</p> <p>PT7FFSDI</p> |



Note: See page P-32 for technical information.

Flush Furniture Feed FRPT, Two-Piece Units

| Description | Catalog Number | Description | Catalog Number |
|--|----------------|--|----------------|
| <p>3-Service Furniture Feed Through-Floor Fitting with (1) ¼ in. EMT stem for power and (2) ½ in. low voltage conduit holes.</p> <p>Specifications:</p> <ul style="list-style-type: none"> • 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) | PT73SD | <p>Single-Service Furniture Feed Through-Floor Fitting with (1) ¼ in. EMT stem for power or low voltage applications.</p> <p>Specifications:</p> <ul style="list-style-type: none"> • For 2¼ to 7 in. floor thickness • UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area | PT71SD |



Service Fittings

| Description | Color | Catalog Number | Description | Color | Catalog Number |
|--|---------------------------------------|---|---|--|---|
| <p>3-Service Furniture Feed Service Fitting</p> <p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> • Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¼ in. threaded hub for power • Painted aluminum flange | <p>Black</p> <p>Gray</p> <p>Ivory</p> | <p>FRF3BK</p> <p>FRF3GY</p> <p>FRF3I</p> | <p>Single-Service Furniture Feed Service Fitting</p> <p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> • Aluminum cover with (1) KO to accept a ¼ in. connector • Painted aluminum flange | <p>Brass Finish</p> <p>Black</p> <p>Gray</p> | <p>FRF1BRS</p> <p>FRF1BK</p> <p>FRF1GY</p> |



Note: See page P-24 for 3 Inch FRPT accessories. See page P-32 for technical information.