



### Complete Line of Raceway

- PolyTrak® Non-Metallic Surface Raceway is a complete system with raceway, fittings, boxes and devices.
- Sizes range from single channel PremiseTrak® to three channel Super BaseTrak® for all types of surface raceway requirements.
- Single and two channel latching raceways are dual-rated for both power and data applications, reducing inventory requirements.
- UL Listed and CSA Certified to 600 volts.
- Office white color.



### Non-Metallic PlugTrak®

- Available as hard wired multi-outlet assembly or relocatable power tap.
- Hubbell designed and manufactured 15 or 20 Amp receptacles.
- UL Listed and CSA Certified.
- Office white color.

#### Hard Wired Multi-Outlet PlugTrak®:

- Available in 5 ft. (1.5m) or 6 ft. (1.8m) lengths.
- Available in single, two circuit and is inherently an isolated ground product.
- Multiple spacing configurations.
- Hard wired PlugTrak® mates with LANTrak® fittings and boxes.
- Tamper-Resistant versions available.

#### Portable PlugTrak®:

- Available in 3 ft. (0.9m) or 5 ft. (1.5m) lengths.
- 6 ft. (1.8m) length 15 or 20 Amp molded cord set allows reliable access.
- Pre-punched holes make mounting easy.



### One Box, Three Systems

- Boxes have three cut-aways that can be utilized with WallTrak®, LANTrak and PremiseTrak (Latching) systems.
- Reduces inventory requirements.
- Eliminates need to order three separate boxes.
- Boxes available in low, standard and deep profiles.
- Two-gang divided box available for power, data, voice, audio and video applications.
- Boxes utilize Hubbell KP plates or Hubbell iSTATION Modules and Bezels.



### Flush or Full Capacity Boxes

- Super BaseTrak® and BaseTrak® Raceway offer multiple solutions for box installation.
- Super BaseTrak® in-line three-gang box allows maximum capacity in a flush design.
- Super BaseTrak® and BaseTrak® available in single, two and three-gang full capacity boxes.
- Two and three channel BaseTrak® (PB2 and PB3) available with one and two-gang in-line boxes.
- Full capacity in-line boxes eliminate the need to de-rate the wire fill capacity due to the intrusion of devices into the raceway channel.

# Non-Metallic Raceway Non-Metallic PlugTrak®

Base and Cover, Portable PlugTrak®, Device Boxes and Fittings



Available in Standard, Isolated Ground (IG), Tamper-Resistant (TR) and USB (U) versions.



USB

Tamper-Resistant

	5 Foot Base and Cover					
	Amp	Circuits	Duplex Recept.	USB Ports	Receptacle Spacing (in.)	Catalog Number
	15	Single	5	—	12	<b>PT155112</b>
	15	Two	5	—	12	<b>PT155212</b>
	15	Single	4	—	15	<b>PT155115</b>
	15	Single	2	—	30	<b>PT155130</b>
	15	TR/Single	5	—	12	<b>PT155112TR</b>
	20	Single	5	—	12	<b>PT205112</b>
	20	Two	5	—	12	<b>PT205212</b>
	20	Single	4	—	15	<b>PT205115</b>
	20	Two	4	—	15	<b>PT205215</b>
	20	Single	2	—	30	<b>PT205130</b>
	20	TR/Single	5	—	12	<b>PT205112TR</b>
	6 Foot Base and Cover					
	15	Single	6	—	12	<b>PT156112</b>
	15	Two	6	—	12	<b>PT156212</b>
	15	Single	4	—	18	<b>PT156118</b>
	15	Single	3	—	24	<b>PT156124</b>
	15	USB/Single	4	4	12	<b>PT156112U</b>
	20	Single	9	—	8	<b>PT206108</b>
	20	Two	9	—	8	<b>PT206208</b>
	20	Single	6	—	12	<b>PT206112</b>
	20	Two	6	—	12	<b>PT206212</b>
	20	Single	4	—	18	<b>PT206118</b>
	20	Two	4	—	18	<b>PT206218</b>
	20	Single	3	—	24	<b>PT206124</b>
20	Two	3	—	24	<b>PT206224</b>	
20	Single	2	—	36	<b>PT206136</b>	

Note: Each Non-Metallic PlugTrak is supplied with one PL1EC end cap and "IG" stickers for isolated ground applications.



	Portable					
	Amp	Length (ft.)	Cord Length (ft.)	Duplex Recept.	USB Ports	Catalog Number
	15	3	6	3	—	<b>PT153112P</b>
	15	5	6	5	—	<b>PT155112P</b>
	15	3	6	4	2	<b>PT153112UP</b>
	20	3	6	2	—	<b>PT203112P</b>
	20	5	6	5	—	<b>PT205112P</b>
	Supporting Mounting Clip for Portable PlugTrak.					<b>PL1MC</b>

Note: Includes ON/OFF switch and circuit breaker.

	Device Boxes			
	Description	Catalog Number	Description	Catalog Number
	1-Gang Low Profile	<b>PDB12LP</b>	1-Gang Deep	<b>PDB12D</b>
1-Gang Standard	<b>PDB12S</b>	2-Gang Deep Divided	<b>PDB12TGD</b>	
Round Lighting Fixture	<b>PDB12LF</b>			
	Fittings			
	Internal Elbow Base and Cover	<b>PL1IEBC</b>	Internal Elbow Cover Only	<b>PL1IE</b>
	External Elbow Base and Cover	<b>PL1EEBC</b>	External Elbow Cover Only	<b>PL1EE</b>
	Flat Elbow Base and Cover	<b>PL1FEBC</b>	Flat Elbow Cover Only	<b>PL1FE</b>
	Tee Base and Cover	<b>PL1TCBC</b>	Tee Cover Only	<b>PL1TC</b>
	Splice Cover	<b>PL1SC</b>	Safety Strap	<b>PL1SS</b>
	Conduit Adapter/Ceiling Fitting	<b>PLP1CACF</b>	End Cap	<b>PL1EC</b>

Note: See page R-56 for additional information.



**PL1MC**  
Supporting Mounting Clip