ACCESSORIES - PNEUMATIC ACTUATOR

Component	Significant	Product
Style	Number	Code

Pilot Solenoids - 110 VAC, 3/4-Way



NEMA 4/4X	SV61CSA110VAC	253055
NEMA 7/9	SV91	253056

Pilot solenoids meet NAMUR mounting specifications.

Pilot Solenoids - 24 VDC, 3/4-Way

	NEMA 4/4X	SV61CSA24VDC	253088
--	-----------	--------------	--------

Pilot solenoids meet NAMUR mounting specifications.

Limit Switches - NEMA 4/4X



Mechanical	MS41-2	253057
Proximity	PS41-2AL	253058

Limit switches include universal mounting brackets (ISO 5211)

Positioners



3-15 psi	PNY01	253061
4 - 20 mA	PEY01	253059
4 - 20 mA, w/ limit switch (LS)	PEY02	253816
4 – 20 mA, w/ position transmitter (PT)	PEY03	253817
4 - 20 mA, w/ LS & PT	PEY04	253818
4 - 20 mA, I-safe	PEI01	253062



All positioners include universal mounting brackets (ISO 5211) and gages.

Several other positioners available, including Intrinsically Safe, Explosion proof, Smart, Stainless Steel and High Vibration models, with limit switch and position transmitter options. Please contact IPEX for more information.

Manual Overide



Sandwich Declutch.	PV01-G0J26	252010
Gearboy ISO 5211	PVU1-GUJ26	253819

Declutchable gearbox has MAXIMUM torque rating of 2600 in-lbs. For higher torque values, please contact IPEX for larger size gearbox models.

Other



Muffler - Brass/Bronze	MUFF-NPT	253065
Speed Control - Brass/Bronze	SPEED-NPT	253066
L-Port Actuator Beacon Kit	BEACON-3W-L	253089
T-Port Actuator Beacon Kit	BEACON-3W-T	253090

Customer must specify at time of order if accessories are to be factory assembled with the actuated valves.