

# TAPPING TEES

## EFS EFS Tapping Tees

IPEX EFS Tapping Tees make for fast and safe installation of service and branch pipe.

Material Class PE4710  
 Field of Application Installation of service and branch pipes to PE pipes 2406/2708 and 3408/4710  
 Range of Application Gas up to 125 psi

- Corrosion-proof construction for long service life
- Leak-proof seals based on hot tapping tee construction
- Easy installation using conventional tooling (no special saddling tools required)
- Best after-market service in the industry with an established North American manufacturer
- Compatible with all Universal Electrofusion Processors



Host Pipe	Branch	Part No.
2 IPS	1/2 CTS	528004
2 IPS	3/4 IPS	528005
2 IPS	1 CTS	528006
2 IPS	1 IPS	528007
2 IPS	1-1/4 CTS	528008
2 IPS	1-1/4 IPS	528009
3 IPS	1/2 CTS	528011
3 IPS	3/4 IPS	528012
3 IPS	1 CTS	528013
3 IPS	1 IPS	528014
3 IPS	1-1/4 CTS	528015
3 IPS	1-1/4 IPS	528016
4 IPS	1/2 CTS	528018

Host Pipe	Branch	Part #
4 IPS	3/4 IPS	528019
4 IPS	1 CTS	528020
4 IPS	1 IPS	528021
4 IPS	1-1/4 CTS	528022
4 IPS	1-1/4 IPS	528023
6 IPS	1/2 CTS	528025
6 IPS	3/4 IPS	528026
6 IPS	1 CTS	528027
6 IPS	1 IPS	528028
6 IPS	1-1/4 CTS	528029
6 IPS	1-1/4 IPS	528030
8 IPS	1/2 CTS	528032
8 IPS	3/4 IPS	528033
8 IPS	1 CTS	528034
8 IPS	1 IPS	528035
8 IPS	1-1/4 CTS	528036
8 IPS	1-1/4 IPS	528037

Requires EFS Tapping Tool - see page 13  
 Allow electrofusion joints to cool prior to handling, pressurizing or tapping.