


Commercial Grade

Candelabra and Medium Base Incandescent Lampholders

Specifications and Features

- Candle sockets for single-light applications
- Fiber Disc Body for use with standard candle tubes
- Spring-tempered steel clip holds Cat. No. 10014-800 socket rigidly in place



4155



9805



10025



10014-800

CANDLE SOCKETS, BOTTOM TURN KNOB

Medium Base Screw Terminals

Description	Rating	Cat. No.
1-Piece Phenolic Body; 2 Leg Bracket; Single Light; Removable Interior; Knurl Nut and Lock Nut	660W 250V	4155
2-Piece Phenolic Husk & Removable Interior Husk; Single Light; Knurl Nut	660W 250V	4158

CANDLE SOCKETS, KEYLESS*

Medium Base Fiber-Disc Body, Screw Terminals

Description	Rating	Cat. No.
Solid Hickey, 2" Overall Height‡	660W 250V	8684
Adjustable Hickey. Overall Height: 4-5 ³ / ₄ "	660W 250	9800

*Insulating paper liner pushes down against Hickey projections.

NOTE: These items are designed for use with standard socket candle tubes (1¹⁵/₁₆" dia.) and require a minimum of 1³/₁₆" dia. flat bottom of candle cup for clearance.

NOM Certified except where indicated by ‡.

CANDLE SOCKETS, PHENOLIC

Medium Base With Removable Turn Knob, Screw Terminals

Description	Rating	Cat. No.
Removable Knob (Short Type), Adjustable Hickey. Overall Height: 4-5 ¹ / ₂ "	250W 250V	9805*
Removable Knob, Removable 1-Leg Hickey. Overall Height: 2 ⁷ / ₁₆ "	250W 250V	9805-A*

NOTE: These items are designed for use with standard socket candle tubes (1¹⁵/₁₆" dia.) and require a minimum of 1³/₁₆" dia. flat at bottom of candle for clearance.

NOM Certified except where indicated by ‡.

CANDELABRA BASE, KEYLESS* ‡

Description	Rating	Cat. No.
Screw Terminals; Solid Hickey. Overall Height: 2"	75W 125V	10025
Screw Terminals; Solid Hickey. Overall Height: 1 ¹ / ₂ "	75W 125V	10027
Screw Terminals; Adjustable Hickey: 3 ¹ / ₄ -4 ³ / ₄ "	75W 125V	10026
Double Snap-In Spring Clips. Height of socket from panel is 1". Leads are No. 18 AWG 105°C plastic, 24" long, stripped 1 ¹ / ₂ "	75W 125V	10014-800

*7/8" candle tube. All Hickeys tapped 1/8 IPS.

TESTING AND CODE COMPLIANCE

- UL Listed (File #E-3810; E-13400)
- CSA Certified (File #LR-1863)
- NOM Certified (File #057)