

# **Residential Grade**

# DC Bus

Leviton created the DC Bus in response to the additional requirements for high quality DC for components in the Structured Media<sup>®</sup> Center. This unique solution reduces clutter and opens up additional space in the Structured Media Enclosure by eliminating the need for more than two AC/DC power adapters. Powered by a single 12VDC adapter and a single 24VDC adapter, the DC Bus provides fully regulated, 12VDC and 24VDC power for several devices.

### **Specifications and Features**

- Contains six 12VDC outputs
- Contains three 24VDC outputs, including one 1 F-connector for coaxial cable connection
- Comes with fully regulated 12V DC & 24V DC AC/DC power adapters
- Power indicating LEDs for both 12VDC and 24VDC inputs
- Comes with 2.1 mm mini power jacks and cords for 12VDC and 1.3 mm mini power jacks for 24VDC

12000	100 C
1	
100	and the second second
1000	
-	
120.00	100
A second	100
100	
<b>E</b>	12.11
100	
200	10.00
11 1	100
10.0	
1000	
	10.40
1000	
-	

48212-124

DC BUS	
Description	Cat. No.
DC Bus - 12VDC & 24VDC	48212-124
Dimensions	2.13" (54.2mm) H x 6.57" (166.8mm) W x 2.43" (61.7mm) D
Input	12VDC and 24VDC AC/DC power adapters (supplied)
Output	Provides 12VDC power at up to 1500 mA total with outlets for five devices.
	Provides 24VDC power at up to 1000 mA total with outlets for three devices,
	including one with F-connector/coaxial cable requirements
Output Power Cables	Included for all but 24 VDC F-connector coaxial connection

Snap-in Modules for Structured Media Center Surge Module Bracket

Leviton's Snap-in Surge Protection Modules provide customized surge protection for all low voltage communication and data lines in the Structured Media Center. All Series 5950 Modules can snap-in to the Cat. No. 3950-BKT Surge Module Bracket. The bracket allows you to add and change modules to fit specific protection needs. Choose from a selection of protection modules for digital Satellite systems, Ethernet systems, cable TV, telephone/fax/modem and DSL/ADSL equipment.

### **Specifications and Features**

- Interchangeable modules accommodate changing surge protection needs
- All modules easily snap into the 3950 Surge Module Bracket
- User friendly design no wiring required
- Telephone/Fax/Modern Module acts as a splitter, allowing the connection of two devices



3950-BKT

## SNAP-IN SURGE PROTECTION BRACKET AND MODULES

Description	Cat. No.
Surge Module Adapter Bracket - For use with Leviton Structured Media Centers	3950-BKT
Satellite System/Cable TV Protection Module - Four standard F-connectors; 3A fuse	Beige: 5951-0SA
for over-current; max. line voltage: 75VDC; breakdown voltage range: 70.4-110 volts/sec	sec Grey: 5951-SAT
	Ice: 5951-SAC