

CAM-TYPE CONNECTORS (UP TO 400A, 600V)

16 Series, Taper Nose

Description	Color	Cat. No. Double Set Screw Style (Cable Size: 1/0-4/0)		Cat. No. Threaded Stud Style .75" L (Cable Size: #2-4/0)		Female w/ Micro Switch
		Male	Female	Male	Female	
		Panel	White	16R21-W	16R22-W	
Receptacles	Black	16R21-E	16R22-E	16R23-E	16R24-E	16RSW-E
	Brown	16R21-H	16R22-H	16R23-H	16R24-H	—
	Red	16R21-R	16R22-R	16R23-R	16R24-R	16RSW-R
	Blue	16R21-B	16R22-B	16R23-B	16R24-B	16RSW-B
	Orange	16R21-O	16R22-O	16R23-O	16R24-O	—
	Green	16R21-G	16R22-G	16R23-G	16R24-G	16RSW-G
	Yellow	16R21-Y	16R22-Y	16R23-Y	16R24-Y	—



16R21-R

Description	Color	Cat. No. Threaded Stud Style 1.125" L (Cable Size: #2-4/0)	
		Male	Female
Panel	White	16R23-11W	16R24-11W
Receptacles	Black	16R23-11E	16R24-11E
	Brown	16R23-11H	16R24-11H
	Red	16R23-11R	16R24-11R
	Blue	16R23-11B	16R24-11B
	Orange	16R23-11O	16R24-11O
	Green	16R23-11G	16R24-11G
	Yellow	16R23-11Y	16R24-11Y



16RSW-G

Description	Color	Cat. No. (Cable Size: #2-4/0) with Half Round Tapped Terminal		Cat. No. Threaded Stud Style (Cable Size: #2-4/0) with Self-Clinching PEM Nuts-Mounting Plate	
		Male	Female	Male	Female
		Panel Mount	White	16R19-W	16R20-W
Receptacles	Black	16R19-E	16R20-E	16R25-11E	16R26-11E
	Brown	—	—	16R25-11H	16R26-11H
	Red	16R19-R	16R20-R	16R25-11R	16R26-11R
	Blue	16R19-B	16R20-B	16R25-11B	16R26-11B
	Orange	—	—	16R25-11O	16R26-11O
	Green	16R19-G	16R20-G	16R25-11G	16R26-11G
	Yellow	—	—	16R25-11Y	16R26-11Y



16R19-E

Description	Color	Cat. No. Angle Style	Cat. No. Offset Style
		Female Terminal Connector (Cable Size: #2-4/0)	White
	Black	16F21-E	16F22-E
	Brown	16F21-H	16F22-H
	Red	16F21-R	16F22-R
	Blue	16F21-B	16F22-B
	Orange	16F21-O	16F22-O
	Green	16F21-G	16F22-G
	Yellow	16F21-Y	16F22-Y



16F21-B

TESTING AND CODE COMPLIANCE

- Meets UL Standards (File #E-13399), Panel Receptacles only
- NEMA 3R-Rated for use outdoors
- CSA Certified (File #152105)