CABLE MANAGEMENT | Fiber Raceway System



Adapts to Any Application

Raceway components are available in three colors (yellow is standard; orange and black are special order), four standard sizes, and a wide variety of styles. Ducting is available solid or slotted, with or without covers; connecting components enable drop-offs and routing around obstacles. Mounting kits allow overhead, raised-floor, and vertical installation.

Assembles Quickly and Easily

Ducting is easily cut to size with a mitre saw, and the system installs with only a screwdriver and other simple carpentry tools. Connection components, including vertical and horizontal outlets and hardware-free covers, snap together tool free, saving time and money. Side drop-off kits can be added after initial installation anywhere along the Raceway to accommodate new cable routing to racks and cabinets.

Preserves Fiber Integrity

High-impact thermoplastic construction ensures ample protection, rigidity, and support. Ducting won't sag under heavy cable loads, and accidental cable damage is prevented, minimizing network downtime. Plus, the system maintains a minimum bend radius of 30 mm at all times.

Reduces Fire Damage

The Fiber Raceway System is UL 2024A listed for riser-rated telecommunications applications. In addition, raceway materials carry one of UL's highest flammability ratings, 94 V-0. They are also halogen-free and produce no corrosive acid or toxic gas emissions in the event of fire, making them ideal for sensitive environments from hospitals and nursing homes to telecom rooms and data centers.

SPOTLIGHT

Fiber Raceway Application Notes



Leviton offers downloadable Fiber Raceway resources, including application notes, Visio® stencils, and a training video, available at Leviton.com/frs. The application notes explain which raceway products or kits are appropriate for specific scenarios, from under-floor mounting to ladder and strut mounting. The video provides installation instructions and a component overview.

Design and product assistance is available via the Tech Support line at 800.824.3005 or at appeng@leviton.com.





DUCTING & BEND RADIUS GUIDES

- 6.5-foot sections can be hand cut to fit exact specifications
- Available in four sizes with two cover types or without covers
- Slotted ducting is ideal for cable runs with varying exit locations
- Bend radius guides safely route fiber

DUCTING						
DESCRIPTION		2" X 2"	4" X 4"	4" X 8"	4" X 12"	
	Solid Duct	S2DCT-SDT	S4DCT-SDT	S8DCT-SDT	SWDCT-SDT	
[A]	Solid Duct and Cover	S2DCT-SDC	S4DCT-SDC	S8DCT-SDC	SWDCT-SDC	
[B]	Slotted Duct	S2DCT-DSL	S4DCT-DSL	_	_	
[C]	Solid Duct and Hinged Cover	S2DCT-DHC+	S4DCT-DHC	S8DCT-DHC	_	
	Slotted Duct and Cover	S2DCT-DCS	S4DCT-DCS	_	_	
	Slotted Duct and Hinged Cover	_	S4DCT-SHC	_	_	

BEND RADIUS GUIDES				
DESCRIPTION	PART NO.			
[D] Radius Guide (10 pack) (fits 2" x 2" and 4" x 4" slotted ducts)	SRAGD-SLT			

Dimensions listed as H x W.

+ = 2"x 2" hinged cover is offered in eight 10" sections only.

2"x 2" is only available in yellow.

Color: Yellow is standard. Orange and Black are special order and require additional lead time.



Please contact inside sales at 800.722.2082 to order or for more information.