

POWER SOLUTIONS



SECTION





SWITCHED SERIES

- Full-featured network management provided via Web, SNMP, and Telnet allows remote access, configuration, and management
- Remote individual outlet control allows shut-down of unused outlets and remote rebooting of attached equipment
- Aggregate current draw can be monitored remotely or locally via digital display
- Power sequencing minimizes in-rush current and prevents circuit overload
- SNMP alerts when power or environmental conditions exceed thresholds
- Firmware is easily upgraded via network download to installed units for future product enhancements
- External probe available separately for relative temperature and humidity monitoring; simply plug it into one of two RJ-11 ports
- Available in vertical Zero-U or horizontal rack-mount styles
- Attaches to most common cabinets and racks with included mounting hardware
- Switched Series includes all features from the Metered Series

METERED SERIES

- Current monitoring helps prevent overloads in high-density computing environments
- Available in vertical Zero-U or horizontal rack-mount styles
- · Horizontal units mount on 19" racks and cabinets
- Included mounting hardware allows attachment to most common cabinets and racks

STANDARDS & CERTIFICATIONS

А

UL 60950-1 LISTED | #E228302

RECOMMENDED APPLICATIONS:

Data Center Cabinets
Telecommunications
Racks



SWITCHED SERIES VERTICAL POWER DISTRIBUTION UNITS (PDUs)							
PART NO.	INPUT			OUTPUT			DIMENSIONS (inches)
	VOLTAGE	AMPS	INPUT CORD TYPE, LENGTH & PLUG	VOLTAGE	RECEPTACLE TYPE	RECEPTACLE QUANTITY	L x W x D
[A] SV161-1D1*	120V	20A	Modular Cord sold separately; see accessories below	120V	5-20R	16	44.4 x 1.75 x 2.25

SWITCHED SERIES HORIZONTAL POWER DISTRIBUTION UNITS (PDUs)							
PART NO.	INPUT			OUTPUT			DIMENSIONS (inches)
	VOLTAGE	AMPS	INPUT CORD TYPE, LENGTH & PLUG	VOLTAGE	RECEPTACLE TYPE	RECEPTACLE QUANTITY	H x W x D
[B] SH081-1D1*	120V	20A	Modular Cord sold separately; see accessories below	120V	5-20R	8	1.75 × 17.0 × 7.0
[C] SH082-1C2	208V	30A	Hardwired; 10' w/L6-30P plug	208V	C13	8	1.75 x 17.0 x 7.0

METERED SERIES HORIZONTAL POWER DISTRIBUTION UNITS (PDUs)							
PART NO.	INPUT			OUTPUT			DIMENSIONS (inches)
	VOLTAGE	AMPS	INPUT CORD TYPE, LENGTH & PLUG	VOLTAGE	RECEPTACLE TYPE	RECEPTACLE QUANTITY	H x W x D
[D] MH101-1D1*	120V	20A	Modular Cord sold separately; see accessories below	120V	5-20R	10	1.75 × 17.5 × 5.0
[E] MH122-1C2	208V	30A	Hardwired; 10' w/L6-30P plug	208V	C13	12	1.75 x 17.5 x 5.0

^{*} = 120V/20A PDUs require a modular power cord.

ACCESSORIES						
DESCRIPTION	PART NO.					
Modular Power Cord, C19 to 5-15P, 10'	PCORD-G10					
Modular Power Cord, C19 to 5-20P, 10'	PCORD-A10					
Modular Power Cord, C19 to L5-20P, 10'	PCORD-H10					
Temperature & Relative Humidity Probe, 10'	TCORD-010					





INPUT PLUG TYPES

NEMA

5-15P 120V

NEMA





5-20P 120V





NEMA

L5-20P 120V L6-30P 208V

OUTPUT RECEPTACLE TYPES

NEMA

IEC 60320





5-20R 120V

C13 208V