

## Floor Box Assembly

Features and Benefits	
<ul style="list-style-type: none"> <li>Complies with NEC 314.27(B)</li> <li>All-in-one, ready-to-wire unit provides quick, easy installation</li> <li>Plate gasket and O-ring combine to seal out moisture and contaminants</li> </ul>	<ul style="list-style-type: none"> <li>Thick brass plate and screw cap resist abuse and prevent contaminants from entering device</li> <li>Durable thermoplastic receptacle face and body resist breakage</li> <li>Brass screw cap threaded to fit flush to plate</li> <li>Backed by a limited 10-year warranty</li> </ul>

Floor Box Assemblies			
Rating		15A-125V	20A-125V
NEMA			
		5-15R	5-20R
Description	Color	Cat. No.	Cat. No.
Duplex, Tamper-Resistant	Brushed Brass	<a href="#">25249-TFB</a>	—
	Nickel Finish	<a href="#">25249-TFN</a>	—
Duplex	Brushed Brass	<a href="#">25249-FBA</a>	<a href="#">25349-FBA</a>
	Nickel Finish	<a href="#">25249-SBA</a>	—
Single	Brushed Brass	<a href="#">5249-FBA</a>	<a href="#">5349-FBA</a>
Single Display Receptacle with Solid Brass Plate	Brushed Brass	<a href="#">5250</a>	—
Floorbox Replacement Screw Cap with O-Ring — Single	Brushed Brass	<a href="#">5249-CAP</a>	—
Floorbox Replacement Screw Cap with O-Ring — Duplex	Brushed Brass	<a href="#">25249-CAP</a>	—



5249-FBA



41650-F

QuickPort® Snap-In Jacks and Modules with Brass Floorplate		
Description	Color	Cat. No.
Floor Jack Housing with Brass Plate and 6-Conductor Jack, 1 blank	Brass	<a href="#">41650-6</a>
Floor Jack Housing with Brass Plate and Coaxial F-Connector, 1 blank	Brass	<a href="#">41650-F</a>
Floor Jack Housing with Brass Plate and two 6-Conductor Jacks	Brass	<a href="#">41652-6</a>
Floor Jack Housing with Brass Plate and Coaxial F-Connector, 6-Conductor Jack	Brass	<a href="#">41652-6F</a>
Floor Jack Housing only, 1 blank filler provided	Brass	<a href="#">41652</a>