





| 15/10A and 20A Wetguard® Straight Blade Devices |        |   |   |  |   |
|---|--------|---|---|--|---|
| Rating  |        | 15A-125V 10A-250V   | 15A-125V  | 15A-250V   | 15A-277V  |
| Configuration                                   |        | 3P 3W   | 2P 3W   | 2P 3W  | 2P 3W   |
| NEMA  |        |  |  |  |  |
|   |        | Non-NEMA  | 5-20  | 6-20   | 24-20   |
| Description                                     | Color  | Cat. No.  | Cat. No.  | Cat. No.   | Cat. No.  |
| Plug  | Yellow | 14W07   | 14W33*  | 14W48  | 14W17   |
| Plug Cap  |        | 14W*  | 14W*  | 14W*   | 14W*  |
| Connector                                       |        | 15W07   | 15W33   | 15W48  | 15W18   |
| Connector Cap                                   |        | 50W50*  | 50W50*  | 50W50*   | 50W50*  |
| Single Outlet                                   |        | 90W07-S   | 90W33-S   | 90W48-S  | —   |
| Duplex Outlet                                   |        | 80W07-D   | —   | —  | —   |
| Single Inlet                                    |        | 59W07   | 59W33   | 59W48  | —   |
| Connector for Single Inlet                      |        | 79W07-C   | 79W33-C   | 79W48-C  | —   |
| Single Receptacle                               |        | —   | 5361-CR   | 5461-CR  | —   |
| Receptacle Cover w/Gasket                       |        | —   | 60W03*  | 60W03*   | —   |

NEMA configuration diagrams represent plug blade configuration.

\*Available in black. To order, add “-B” suffix to catalog number



14W07



14W



90W48

### SPOTLIGHT

#### Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit [www.leviton.com/wetguard](http://www.leviton.com/wetguard) for more information.



## Straight Blade Plugs, Connectors, Inlets, Outlets and Receptacles

### Product Overview

#### Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

#### Wetguard® Watertight Straight Blade Devices



Plug



Plug Cap



Connector



Connector Cap



Single Outlet



Duplex Outlet



Single Inlet



Connector for Single Inlet



Single Receptacle



Receptacle Cover

## WETGUARD® STRAIGHT BLADE DEVICES | 15A | 15/10A and 20A

### Straight Blade Devices — 15A

| 15A Wetguard® Straight Blade Devices |      |                    | Cat. No. |          |           |               |               |               |              |                            |                   |                           |
|--------------------------------------|------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| Amp                                  | Volt | NEMA Configuration | Plug     | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| <b>2-Pole, 2-Wire</b>                |      |                    |          |          |           |               |               |               |              |                            |                   |                           |
| 15                                   | 125  | 1-15               | 14W04    | 14W*     | 15W04     | 50W50*        | 90W04-S       | 80W04-D       | 59W04        | 79W04-C                    | —                 | —                         |
| <b>2-Pole, 3-Wire</b>                |      |                    |          |          |           |               |               |               |              |                            |                   |                           |
| 15                                   | 125  | 5-15               | 14W47*   | 14W*     | 15W47*    | 50W50*        | 90W47-S       | 80W47-D       | 59W47        | 79W47-C                    | 5261-CR           | 60W03*                    |
| 15                                   | 250  | 6-15               | 14W49    | 14W*     | 15W49     | 50W50*        | 90W49-S       | 80W49-D       | 59W49        | 79W49-C                    | 5661-CR           | 60W03*                    |
| 15                                   | 277  | 7-15               | 14W34    | 14W*     | 15W34     | 50W50*        | —             | —             | —            | —                          | —                 | —                         |
| 15                                   | 347  | 24-15              | 14W15    | —        | 15W16     | 50W50*        | —             | —             | —            | —                          | —                 | —                         |

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add “-B” suffix to catalog number

### Straight Blade Devices — 15A and 20A

| 15/10A and 20A Wetguard® Straight Blade Devices |            |                    | Cat. No. |          |           |               |               |               |              |                            |                   |                           |
|---|------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| Amp   | Volt       | NEMA Configuration | Plug     | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| <b>3-Pole, 3-Wire</b>                           |            |                    |          |          |           |               |               |               |              |                            |                   |                           |
| 15<br>10  | 125<br>250 | Non-NEMA           | 14W07    | 14W*     | 15W07     | 50W50*        | 90W07-S       | 80W07-D       | 59W07        | 79W07-C                    | —                 | —                         |
| <b>2-Pole, 3-Wire</b>                           |            |                    |          |          |           |               |               |               |              |                            |                   |                           |
| 20  | 125        | 5-20               | 14W33*   | 14W*     | 15W33     | 50W50*        | 90W33-S       | —             | 59W33        | 79W33-C                    | 5361-CR           | 60W03*                    |
| 20  | 250        | 6-20               | 14W48    | 14W*     | 15W48     | 50W50*        | 90W48-S       | —             | 59W48        | 79W48-C                    | 5461-CR           | 60W03*                    |
| 20  | 347        | 24-20              | 14W17    | 14W*     | 15W18     | 50W50*        | —             | —             | —            | —                          | —                 | —                         |

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add “-B” suffix to catalog number

#### SPOTLIGHT Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit [www.leviton.com/wetguard](http://www.leviton.com/wetguard) for more information.

