30A, 50A, 60A | Power Devices

30A, 50A and 60A Devices

Industrial Grade Power Devices

Built from durable thermoplastic, Leviton power receptacles — in flush mount, surface mount and panel mount versions — come equipped with heavy-gauge, double-wire copper alloy contacts. To ensure correct and speedy wiring, terminals have ID markings. Flush mount receptacles fit Leviton's wide range of 2.15"-diameter wallplates and mounting hardware is included. Angle plugs are made of tough, heavy-duty nylon for a long dependable service life.

279-PM, 5054 and 279



Features and Benefits

- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to #4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes
- Surface-mount devices are commercial grade and have concentric knockouts for 3/4" and 1" conduit and adjustable cord clamp for back and bottom entrance of cable

Angle Plugs

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4 AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity



n



30A, 50A, 60A | Power Devices

Continued from previous page

| 3-Pole, 4-Wire, 3 Phase, Grounding ® ® | | | | | | |
|--|----------|----------|---|--|--|--|
| Rating | 60A-250 | | | | | |
| NEMA | | | | | | |
| | 15-60P | 15-60R | | | | |
| Description | Cat. No. | Cat. No. | Wallplate Information | | | |
| Flush Mount Receptacle | _ | 8460 | Fits any wallplate with 2.465" diameter center hole | | | |
| Angle Plug | 8462-P | _ | | | | |



8462-P

| 4-Pole, 4-Wire, 3 Phase, Non-Grounding ® ® | | | | |
|--|----------|------------------|---|--|
| Rating | 30A-120/ | 30A-120/208V 3ØY | | |
| NEMA | | | | |
| | 18-30P | 18-30R | | |
| Description | Cat. No. | Cat. No. | Wallplate Information | |
| Flush Mount Receptacle | _ | 8330 | Fits any wallplate with 2.465" diameter center hole | |
| Angle Plug | 8332-P | _ | | |
| Rating | 50A-120/ | 208V 3ØY | | |
| NEMA | 18-50P | 18-50R | | |
| Description | Cat. No. | Cat. No. | Wallplate Information | |
| Flush Mount Receptacle | _ | 8350 | Fits any wallplate with 2.465" diameter center hole | |
| Angle Plug | 8352-P | _ | | |
| Rating | 60A-120/ | ′208V 3ØY | | |
| NEMA | | | | |
| | 18-60P | 18-60R | | |
| Description | Cat. No. | Cat. No. | Wallplate Information | |
| Flush Mount Receptacle | _ | 8360 | Fits any wallplate with 2.465" diameter center hole | |
| Angle Plug | 8362-P | _ | | |



8330

8350



8362-P