

Combination Devices

RESIDENTIAL



DECORA® | 15A, 20A

Continued from previous page

15A, 20A Combination Switches*

Rating	Switch: 15A-120VAC Pilot Light: 1/25W-125VAC		
Description	Color	Cat. No.	
3-Way Switch/ Receptacle	White	5645-W	
	Ivory	5645-I	
	Black	5645-E	

Rating	Individual Switches: 15A-120V Device Total: 20A-120V		Individual Switches: 15A-120V Device Total: 20A-120V	
Description	Color	Cat. No. Non-grounded	Cat. No. with Ground Screw	
Dual Rockers	White	1754-W	1754-2W	
	Ivory	1754-I	—	
	Light Almond	1754-T	—	
Illuminated Dual Rockers (Light is ON when top rocker is OFF)	White	1754-ILW	—	
	Ivory	1754-ILI	—	
Three Rockers	White	1755-W	1755-2W	
	Ivory	1755-I	1755-2I	
	Light Almond	1755-T	—	



1755-W

*Warning: Although each individual rocker switch is rated up to 15A-120V, the total combined load for both duplex or all three triplex switches must not exceed 20 Amps

Decora® USB Charger Combination Devices

15A, 20A USB Charger Combination Switches

Rating	USB Port: 3.6A Receptacle: 15A-125V		USB Port: 3.6A Receptacle: 20A-125V	
Description	Color	Cat. No.	Cat. No.	
USB Charger/ Tamper-Resistant Receptacle	White	T5631-2W	—	
	Light Almond	T5631-T	—	
	Black	T5631-E	—	
USB Charger/Duplex Tamper-Resistant Receptacle	White	T5632-W	T5832-W	
	Ivory	T5632-I	T5832-I	
	Light Almond	T5632-T	T5832-T	
	Black	T5632-E	T5832-E	
	Gray	T5632-GY	T5832-GY	
	Brown	T5632-B	—	
	Hospital Grade	White	T5632-HGW	T5832-HGW
USB Charger/Duplex Tamper-Resistant Receptacle	Ivory	T5632-HGI	T5832-HGI	
	Light Almond	T5632-HGT	T5832-HGT	
	Black	T5632-HGE	T5832-HGE	
	Gray	T5632-HGG	T5832-HGG	
	Brown	T5632-HG	T5832-HG	
	Red	T5632-HGR	T5832-HGR	

Rating	USB Port: 4.2A	
Description	Color	Cat. No.
4-Port USB Charger	White	USB4P-W
	Ivory	USB4P-I
	Light Almond	USB4P-T
	Black	USB4P-E
	Gray	USB4P-GY



T5632-HGW



T5832-W



USB4P-W

