

15A | Watertight

Wetguard® Watertight Locking Plugs, Connectors, Inlets, Outlets and Receptacles

Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

15A Wetguard® Locking Devices

| Rating | 15A-125V | 15A-125V | 15A-250V | 15A-277V | |
|----------------------------|----------|----------|----------|----------|----------|
| Configuration | 2P 2W | 2P 3W | 2P 3W | 2P 3W | |
| NEMA | L1-15 | L5-15 | L6-15 | L7-15 | |
| Description | Color | Cat. No. | Cat. No. | Cat. No. | Cat. No. |
| Plug | Yellow | 24W04 | 24W47* | 24W49 | 24W34 |
| Plug Cap | | 14W* | 14W* | 14W* | 14W* |
| Connector | | 25W04 | 25W47* | 25W49 | 25W34 |
| Connector Cap | | 50W50* | 50W50* | 50W50* | 50W50* |
| Single Outlet | | 95W04-S | 95W47-S | 95W49-S | 95W34-S |
| Duplex Outlet | | 85W04-D | 85W47-D | 85W49-D | 85W34-D |
| Single Inlet | | 64W04 | 64W47 | 64W49 | 64W34 |
| Connector for Single Inlet | | 74W04-C | 74W47-C | 74W49-C | 74W34-C |
| Single Receptacle | | — | 47CM-10 | 45CM-60 | 47CM-60 |
| Receptacle Cover w/Gasket | | — | 60W03* | 60W03* | 60W03* |



24W04



50W50

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add “-B” suffix to catalog number

SPOTLIGHT

Wetguard® Watertight Wiring Devices

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.



Locking Plugs, Connectors, Inlets, Outlets and Receptacles

Product Overview

Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

Wetguard® Watertight Locking Devices



Plug



Plug Cap



Connector



Connector Cap



Single Outlet



Duplex Outlet



Single Inlet



Connector Mates w/Inlet



Single Receptacle



Receptacle Cover

WETGUARD® LOCKING DEVICES | 15A | 15/10A and 20A

Locking Devices – 15A

| 15A Wetguard® Locking Devices | | | | | | | | | | | | |
|-------------------------------|------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| | | | Cat. No. | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| 2-Pole, 2-Wire | | | | | | | | | | | | |
| 15 | 125 | L1-15 | 24W04 | 14W* | 25W04 | 50W50* | 95W04-S | 85W04-D | 64W04 | 74W04-C | — | — |
| 2-Pole, 3-Wire | | | | | | | | | | | | |
| 15 | 125 | L5-15 | 24W47* | 14W* | 25W47* | 50W50* | 95W47-S | 85W47-D | 64W47 | 74W47-C | 47CM-10 | 60W03* |
| 15 | 250 | L6-15 | 24W49 | 14W* | 25W49 | 50W50* | 95W49-S | 85W49-D | 64W49 | 74W49-C | 45CM-60 | 60W03* |
| 15 | 277 | L7-15 | 24W34 | 14W* | 25W34 | 50W50* | 95W34-S | 85W34-D | 64W34 | 74W34-C | 47CM-60 | 60W03* |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add "-B" suffix to catalog number

Locking Devices – 15/10A and 20A

| 15/10A and 20A Wetguard® Locking Devices | | | | | | | | | | | | |
|--|------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|
| | | | Cat. No. | | | | | | | | | |
| Amp | Volt | NEMA Configuration | Plug | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |
| 3-Pole, 3-Wire | | | | | | | | | | | | |
| 15 10 | 125 250 | Non-NEMA | 24W07 | 14W* | 25W07 | 50W50* | 95W07-S | 85W07-D | 64W07 | 74W07-C | — | — |
| 2-Pole, 2-Wire | | | | | | | | | | | | |
| 20 | 250 | L2-20 | 26W07 | 26W* | 27W07 | 50W50* | 97W07-S | 87W07-D | 66W07 | 76W07-C | — | — |

NEMA configuration diagrams represent plug blade configuration.
 *Available in black. To order, add "-B" suffix to catalog number

SPOTLIGHT Wetguard® Watertight

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit www.leviton.com/wetguard for more information.

