





## 20A AND 20/10A | Watertight

Continued from previous page

### Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

20A and 20/10A Wetguard® Locking Devices						
Rating	20A-125/250V	20A-3Ø 250V	20A-3Ø 480V	20A-3ØY 120/208V		
Configuration	3P 4W	3P 4W	3P 4W	4P 4W		
NEMA	 L14-20	 L15-20	 L16-20	 Non-NEMA		
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.	
Plug	Yellow	26W74	26W75*	26W76*	26W09	
Plug Cap		26W*	26W*	26W*	26W*	
Connector		27W74	27W75*	27W76*	27W09	
Connector Cap		50W52*	50W52*	50W52*	50W52*	
Single Outlet		97W74-S	97W75-S	97W76-S	97W09-S	
Duplex Outlet		—	—	—	—	
Single Inlet		66W74	66W75	66W76	66W09	
Connector for Single Inlet		76W74-C	76W75-C	76W76-C	76W09-C	
Single Receptacle		24CM-10	24CM-20	24CM-30	7410-B	
Receptacle Cover w/Gasket		60W04*	60W04*	60W04*	60W04*	
Rating		20A-3ØY 120/208V	20A-3ØY 277/480V	20A-3ØY 347/600V	20A-250V 10A-600V	
Configuration		4P 5W	4P 5W	4P 5W	4P 5W	
NEMA		 L21-20	 L22-20	 L23-20	 Non-NEMA	
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.	
Plug	Yellow	26W81*	26W82	26W83	26W10	
Plug Cap		26W*	26W*	26W*	26W*	
Connector		27W81*	27W82	27W83	27W10	
Connector Cap		50W52*	50W52*	50W52*	50W52*	
Single Outlet		97W81-S	97W82-S	97W83-S	97W10-S	
Duplex Outlet		—	—	—	—	
Single Inlet		66W81	66W82	66W83	66W10	
Connector for Single Inlet		76W81-C	76W82-C	76W83-C	76W10-C	
Single Receptacle		2510	2520	2530	—	
Receptacle Cover w/Gasket		60W04*	60W04*	60W04*	60W04*	

NEMA configuration diagrams represent plug blade configuration.  
\*Available in black. To order, add "-B" suffix to catalog number



26W74



66W76



26W



27W81



#### Related Products

See section H for more information on the entire line of watertight wiring devices.

## Locking Plugs, Connectors, Inlets, Outlets and Receptacles

### Product Overview

#### Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

#### Wetguard® Watertight Locking Devices



Plug



Plug Cap



Connector



Connector Cap



Single Outlet



Duplex Outlet



Single Inlet



Connector Mates w/Inlet



Single Receptacle



Receptacle Cover

**WETGUARD® LOCKING DEVICES | 20A and 20/10A**
**Locking Devices — 20A and 20/10A**

20A and 20/10A Wetguard® Locking Devices													
			Cat. No.										
Amp	Volt	NEMA Configuration	Plug	Plug Cap	Connector	Connector Cap	Single Outlet	Duplex Outlet	Single Inlet	Connector for Single Inlet	Single Receptacle	Receptacle Cover w/Gasket	
<b>2-Pole, 3-Wire</b>													
20	125	L5-20	26W47*	26W*	27W47*	50W52*	97W47-S	—	66W47	76W47-C	23CM-10	60W04*	
20	250	L6-20	26W48*	26W*	27W48*	50W52*	97W48-S	—	66W48	76W48-C	23CM-20	60W04*	
20	277	L7-20	26W49	26W*	27W49	50W52*	97W49-S	—	66W49	76W49-C	23CM-30	60W04*	
20	347	L24-20	22W07	26W*	23W07	50W52*	93W07-S	—	68W29	78W29-C	—	—	
<b>3-Pole, 3-Wire</b>													
20	125/ 250	Non-NEMA	26W08	26W*	27W08	50W52*	97W08-S	—	66W08	76W08-C	7310-B	60W04*	
20	250	Non-NEMA	26W08-G	26W*	27W08-G	50W52*	—	—	—	—	—	—	
10	600	Non-NEMA	—	—	—	—	—	—	—	—	—	—	
<b>3-Pole, 4-Wire</b>													
20	125/ 250	L14-20	26W74	26W*	27W74	50W52*	97W74-S	—	66W74	76W74-C	24CM-10	60W04*	
20	3Ø 250	L15-20	26W75*	26W*	27W75*	50W52*	97W75-S	—	66W75	76W75-C	24CM-20	60W04*	
20	3Ø 480	L16-20	26W76*	26W*	27W76*	50W52*	97W76-S	—	66W76	76W76-C	24CM-30	60W04*	
<b>4-Pole, 4-Wire</b>													
20	3ØY 120/208	Non-NEMA	26W09	26W*	27W09	50W52*	97W09-S	—	66W09	76W09-C	7410-B	60W04*	
<b>4-Pole, 5-Wire</b>													
20	3ØY 120/208	L21-20	26W81*	26W*	27W81*	50W52*	97W81-S	—	66W81	76W81-C	2510	60W04*	
20	3ØY 277/480	L22-20	26W82	26W*	27W82	50W52*	97W82-S	—	66W82	76W82-C	2520	60W04*	
20	3ØY 347/600	L23-20	26W83	26W*	27W83	50W52*	97W83-S	—	66W83	76W83-C	2530	60W04*	
20	250	Non-NEMA	26W10	26W*	27W10	50W52*	97W10-S	—	66W10	76W10-C	—	60W04*	
10	600	Non-NEMA	—	—	—	—	—	—	—	—	—	—	

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add “-B” suffix to catalog number