LEVITON®

RHINO-HIDE® SINGLE POLE | Cam-Type Devices

Rhino-Hide® Single Pole Cam Devices

Single Pole Cam-Type Devices

Rhino-Hide® Single Pole Cam-Type Devices from Leviton are designed to provide superior service and durability, even under the most severe operating conditions. Our 15 Series Taper Nose mini-cam plugs and receptacles are rated to 150 Amps, making them ideal for entertainment applications such as those found at carnivals and theme parks.

Our 16 Series Taper Nose Cam-Type Devices are rated up to 400 Amps, making them the devices of choice for power distribution applications such as construction sites, mining operations, welding, cell tower backup power, concerts, sound stages, movie making, television productions, sporting events and conventions.

The 18 Series Single Pole Ball Nose Cam-Type Devices are also rated to 400 Amps, and are typically favored by the broadcasting and welding industries as well as many end users in Canada. All of these devices feature solid brass contacts and high-performance TPV insulators, making them ideal for both outdoor and indoor applications. The positive locking connection maintains its integrity even when subjected to vibration. Plus, they are interoperable and interchangeable with competitive products.

Our 17 & 19 Series Taper and Ball Nose devices are rated up to 690 Amps and can withstand grueling, heavy-duty industrial use. Preferred applications for these series include generator test stations, water purification plants, electrochemical machining equipment and other general industrial uses.

Leviton's Rhino-Hide® 22 & 23 Series Single Pole Latching Cam-Type devices are also rated up to 690 Amps and feature an additional latching mechanism for added security, especially in high-vibration applications. These devices can also be retrofitted to existing locations and power distribution systems, allowing for an effortless installation. The 22 Series Plugs offer an innovative solution for all tower-to-cell cable connections in wind turbines. Our In-Line Cam-Type Plugs partnered with pre-assembled harnesses allow quick connect and disconnect on site. In addition, when compared to traditional "butt-splice" methods, cam plugs lower total installation costs drastically. These plugs are commonly used to provide power to ships at dock side, and are recognized by ETL Labs to meet U.S. Navy specifications.

49 Series Single Pole High Amperage Devices

Rhino-Hide® 49 Series single pole devices are designed to deliver up to 1135 Amps at 1000 volts, AC or DC, under the most extreme conditions with cables ranging in size from 313 MCM to 777 MCM. Leviton's Rhino-Hide® products are designed to mate with other manufacturers' high-amperage single pole devices. Rhino-Hide® 49 Series single pole high-amperage devices are CE Certified and cURus recognized components engineered to exceptional standards for high-amperage power delivery.

Rhino-Hide® 49 Series products are ideal for any number of demanding applications requiring continuous, reliable high-amperage power in multi phases. Typical locations where these products are used include oil and gas rigs as well as heavy industrial applications. Rhino-Hide® devices can be installed on both existing silicon-controlled rectifiers (SCRs) and generator stations or on new oil and gas rig construction. These devices are used by SCR drive manufacturers and top drive manufacturers to distribute power from the SCR to mud pumps and top drives.



RHINO-HIDE® SINGLE POLE | Cam-Type Connectors

Cam-Type Devices

Features and Benefits

Cam-Type Devices for Commercial and Industrial Use

Rhino-Hide® Single Pole Cam-Type Connectors from Leviton supply temporary electrical power distribution for multiple indoor and outdoor applications.

Common Applications

- Motor and generator splices
- Mining and construction sites
- Commercial and navy shipbuilding and repair
- Other temporary power applications

Leviton Cam-Type Devices

- Plugs are available in set screw or crimp tube termination, taper nose and ball nose configurations
- Intermateable and compatible with competitive cam-type products can be retrofitted to existing locations and power distribution systems
- Shatter and crack proof high durometer thermoplastic vulcanizate (TPV) or Neoprene™ rubber
- Color-coded insulating sleeves provide fast and easy phase identification
- Self compensating for wear slit in male contact provides spring action for longer usage
- Quick connect/disconnect
- High conductivity positive, vibration-proof connection provided by cam design
- Wide range of applications usable with a wide range of cable and amperage ratings
- Meets NEC requirements and is UL Listed and CSA Certified; NEMA 3R-rated for use in outside locations

Experience the Difference

Rhino-Hide® Single Pole Cam-Type Connectors are designed for easy assembly and disassembly without special tools. A thermoplastic screw is used to tightly secure the contact inside the insulating sleeve, making assembly, disassembly and field repairs effortless. The plugs use plastic locking and reinforcement rings molded into insulating sleeves and receptacles, ensuring the integrity of the connection. Under severe stress and load conditions, these rings will not melt, break or crack.

Single Pole Group





RHINO-HIDE® SINGLE POLE | Cam-Type Connectors

Cam-Type Plugs

Sample Cam-Type Components



Self compensating for wear slit and in male contact provides spring action for longer usage

Hard thermoplastic screw provides strength and durability Intermateable and with competitive cam-type products — can be retrofitted to existing locations and power distribution systems

Color Choices Rhino-Hide® Cam-Type devices are offered in a wide range of colors. To order colors, add suffix to Cat. No.



















Cam-Type Plugs							
Connector Type	Component	Description	Standards and Certifications (NEMA, UL, CSA)				
15, 16, 18	Sleeve*	Thermoplastic Vulcanizate (TPV)	See individual pages throughout this section for				
Series Plugs	Contact	Brass	specific Standards and Certifications information				
	Strain-Relief	Copper Wire					
17, 19, 22/23	Sleeve**	Neoprene™	See individual pages throughout this section for				
Series Plugs	Contact	Brass	specific Standards and Certifications information				
	Strain-Relief	Copper Wire	1				

^{*&}quot;V" Series Neoprene™.

^{**22}L22-S and 22L25-S Series: TPV



RHINO-HIDE® SINGLE POLE | 15 Series | Plugs | Replacement Sleeves

15 Series

Taper Nose, Cam-Type Plugs

150A, 600VAC/DC Max — NEMA 3R Rated for Outdoor Use

The 15 Series Taper Nose mini-cam plugs, receptacles and connectors are tough and reliable. Primary applications include carnivals and theme parks, as well as the entertainment industry.

15 Series Cam-Type Plugs (up to 150A, 600V) — UL/CSA 1691 Listed

		Male Plug	Female Plug
Description	Color	Cat. No.	Cat. No.
Single Set Screw Termination	White	15D21-UW	15D22-UW
Cable Size: #8 - #2	Black	15D21-UE	15D22-UE
Max Ampacity: 150A	Brown	15D21-UH	15D22-UH
Voltage: 600VAC/DC	Red	15D21-UR	15D22-UR
	Blue	15D21-UB	15D22-UB
	Orange	15D21-U0	15D22-U0
	Green	15D21-UG	15D22-UG
	Yellow	15D21-UY	15D22-UY
Replacement Contacts	_	15D21-UC	15D22-UC
Crimp Tube Termination	White	15D23-UW	15D24-UW
Cable Size: #8 - #4	Black	15D23-UE	15D24-UE
Max Ampacity: 140A	Brown	15D23-UH	15D24-UH
Voltage: 600VAC/DC	Red	15D23-UR	15D24-UR
	Blue	15D23-UB	15D24-UB
	Orange	15D23-U0	15D24-U0
	Green	15D23-UG	15D24-UG
	Yellow	15D23-UY	15D24-UY
Replacement Contacts	_	15D23-UC	15D24-UC



15D22-UG



15D23-UW



15D24-UG

15 Series — Replacement Sleeves						
		Male	Female			
Description	Color	Cat. No.	Cat. No.			
Sleeves	White	15SDM-1UW	15SDF-1UW			
	Black	15SDM-1UE	15SDF-1UE			
	Brown	15SDM-1UH	15SDF-1UH			
	Red	15SDM-1UR	15SDF-1UR			
	Blue	15SDM-1UB	15SDF-1UB			
	Orange	15SDM-1U0	15SDF-1U0			
	Green	15SDM-1UG	15SDF-1UG			
	Yellow	15SDM-1UY	15SDF-1UY			

Note: Contact factory for availability



Related Products

To accommodate everyday use Leviton offers a variety of 15 Series accessories. See page J-24 for more information.