

LINEAR FLUORESCENT | Medium and Miniature Bi-Pin Lamp

Medium and Miniature Bi-Pin Linear Fluorescent Lampholders

Features and Benefits

Lamp-Lock

- Four-position lamp-lock socket rotates 90° forward and back, for quick relamping
- Lamp-lock models have slim, low profile silhouette that fits 22- to 25- gauge panels
- Chemical-resistant white thermoplastic body

T-8 to T-5 Adapter

• Cost-effective solution to incorporate miniature bi-pin T-5 lamps into existing T-8 fixtures

For Medium Bi-Pin Lamps — Slide-On Design and Lamp-Lock 🕦 🕦			
Description	Rating	Cat. No.	
Low Profile 0.64 (16.3mm) Lamp Center Snap-In or Slide-On Mounting Featuring Lamp Lock for T-8 Lamps Only	660W 600V	13662	
Same as 13662, Except with Internal Shunt Connection for Electronic Ballasts	660W 600V	23662	
Medium Profile 0.91 (23.0) Lamp Center Snap-In or Slide-On Mounting Featuring Lamp Lock for T-8 and T-12 Lamps	660W 600V	13661	
Same as 13661, Except with Internal Shunt Connection for Electronic Ballasts	660W 600V	23661	
Tall Profile 1.18 (30.0) Lamp Center Snap-In or Slide-On Mounting Featuring Lamp Lock for T-8 and T-12 Lamps	660W 600V	13660	
Same as 13660, Except with Internal Shunt Connection for Electronic Ballasts	660W 600V	23660	



13661



23662

	Dedicated T-8 Fluorescent Lampholder — Provides Straight-In Lamping 🕒 🕦		
	Description	Rating	Cat. No.
	Straight-In Medium Bi-Pin Fluorescent Lampholder	600W 600V, Thermoplastic body,	13280
	for T-8 lamps with a G13 Base. Non-shunted	PBT material rated 130°C, 94V-0	
Ī	Same as 13280, except with internal shunt	600W 600V, Thermoplastic body,	23280
	connection for instant-start ballasts	PBT material rated 130°C, 94V-0	



23280

