

TRADITIONAL

Traditional Wallplates

Familiar and functional, Leviton traditional wallplates are designed for use with traditional Leviton devices. They represent styles and form factors that have stood the test of time. Their clean lines work in virtually any location, whether in new or retrofit construction, and they install quickly and easily. Leviton offers traditional wallplates in a vast array of colors and configurations.

Sample Traditional Wallplates



Features and Benefits

All Leviton Wallplates

- Easy to clean, smooth finish
- Non-combustible
- Color-matched metal mounting screws supplied
- UL Listed and CSA Certified
- Conforms to NEMA and ANSI standards
- Backed by a limited 10-year warranty

Thermoset (Plastic) Wallplates (Residential Grade)

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL 514 testing requirements
- Resistant to fading, discoloration, grease, oil, organic solvents, moisture and scratches

Thermoplastic (Nylon) Wallplates (Residential/Commercial Grade)

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications

Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick brushed finish
- Standard stainless steel Type 430, .032" thick, also available brushed finish
- Brass is 70/30 alloy 260, .040" thick polished or brushed finish

Antimicrobial

- All antimicrobial devices use silver ions (Ag+) as the antimicrobial agent in the product material
- Antimicrobial material has been tested to show a consistent {3 log (>99.9%)} microbial reduction rate against a broad range of bacteria pursuant to the JIS Z 2801:2000 test protocol

Color Choices

Traditional wallplates are offered in a wide range of colors and finishes. To order colors, add suffix to Cat. No.



Ivory



(-W)



(-G/-GY)

Black

Brown







Blue (-B)



(-0)

Polished Brass (-PB)

Satin-Finish Stainless



Brushed

Brass

Chrome



TRADITIONAL | Power Outlet Receptacles

Continued from previous page

Power Outlet Receptacles

			Thermoplastic (Nylon)	Metal	
Description	Color	Cat. No.	Cat. No.	Material Type	Cat. No.
30A and 50A	White	80526-W	80726-W	Aluminum	83026
Receptacle,	Ivory	80526-l	80726-I	Gray Painted Steel	4934
2.15" dia.	Lt. Almond	80526-T	_	Stainless Steel	84026
	Black	80526-BLK	_		
	Brown	_	80726		
30A and 50A	White	80530-W	_	Gray Painted Steel	S701-GY
Receptacle,	Ivory	80530-l	_	Non-Magnetic S/S	S701-40
• 2.465" dia. hole	Lt. Almond	80530-T	_	-	
	Black	80530-BLK	_		
. 30A and 50A				Stainless Steel	84022
Receptacle,					
2.15" dia, hole offset					

Note: Use with 278, 279, 5206, 5207, 5371, 5372, 5374

Standard Size Metal — 2-Gang with Centered Opening ® ®							
	Metal						
Description	Material Type	Cat. No.					
1-Decora®	Non-Magnetic S/S	S746-N					
1-Toggle	Brass Non-Magnetic S/S	81040 84040-40					
1-Duplex	Non-Magnetic S/S	84039-40					
1-Outlet 1.406" dia. hole	Non-Magnetic S/S	84092-40					

Standard Size Louvre ® ®								
		Painted Steel	Metal					
	Description	Color	Cat. No.	Material Type	Cat. No.			
· \	1-Gang, Center Horizontal, Strap Mount	White Ivory	88079 86079	Brass Non-Magnetic S/S	81079 84079-40			
	1-Gang Vertical, Strap Mount	White Ivory	88080 86080	Brass Non-Magnetic S/S	81080 84080-40			
	2-Gang, 2-Louvre, Vertical, Strap Mount			Non-Magnetic S/S	84081-40			