

TRADITIONAL

Traditional Wallplates

Familiar and functional, Leviton traditional wallplates are designed for use with traditional Leviton devices. They represent styles and form factors that have stood the test of time. Their clean lines work in virtually any location, whether in new or retrofit construction, and they install quickly and easily. Leviton offers traditional wallplates in a vast array of colors and configurations.

Sample Traditional Wallplates



Features and Benefits

All Leviton Wallplates

- Easy to clean, smooth finish
- Non-combustible
- Color-matched metal mounting screws supplied
- UL Listed and CSA Certified
- Conforms to NEMA and ANSI standards
- Backed by a limited 10-year warranty

Thermoset (Plastic) Wallplates (Residential Grade)

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL 514 testing requirements
- Resistant to fading, discoloration, grease, oil, organic solvents, moisture and scratches

Thermoplastic (Nylon) Wallplates (Residential/Commercial Grade)

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications

Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick brushed finish
- Standard stainless steel Type 430, .032" thick, also available brushed finish
- Brass is 70/30 alloy 260, .040" thick polished or brushed finish

Antimicrobial

- All antimicrobial devices use silver ions (Ag+) as the antimicrobial agent in the product material
- Antimicrobial material has been tested to show a consistent {3 log (>99.9%)} microbial reduction rate against a broad range of bacteria pursuant to the JIS Z 2801:2000 test protocol

Color Choices

Traditional wallplates are offered in a wide range of colors and finishes. To order colors, add suffix to Cat. No.



Ivory



(-W)



(-G/-GY)

Black

Brown







Blue (-B)



(-0)

Polished Brass (-PB)

Satin-Finish Stainless



Brushed

Brass

Chrome



TRADITIONAL | Single Receptacle | Telephone or Cable Outlet

Single Receptacle

15A and 20A Straight Blade and 15A Locking (1.406" Diameter Hole)

| | | Th | ermoset (Pla | astic) | Thermoplas | tic (Nylon) | | Metal | | |
|-------------|------------|----------------------|--------------------|----------------------|----------------------|--------------------|------------------|----------------------|--------------------|----------------------|
| Description | Color | Cat. No. STANDARD | Cat. No. MIDWAY | Cat. No. OVERSIZE | Cat. No. STANDARD | Cat. No. MIDWAY | Material Type | Cat. No. STANDARD | Cat. No. MIDWAY | Cat. No. OVERSIZE |
| 1-Gang | White | 88004 | 80504-W | _ | 80704-W | PJ7-W | Aluminum | 83004 | _ | _ |
| | lvory | 86004 | 80504-I | _ | 80704-1 | PJ7-I | Brass | 81004 | _ | - |
| . | Lt. Almond | 78004 | 80504-T | _ | 80704-T | PJ7-T | Non-Magnetic S/S | 84004-40 | SSJ7-40 | 84104-40 |
| <u> </u> | Gray | _ | _ | _ | 80704-GY | _ | | | | |
| | Black | _ | _ | _ | 80704-E | _ | | | | |
| | Brown | 85004 | 80504 | _ | 80704 | _ | | | | |
| | Red | _ | _ | _ | 80704-R | PJ7-R | | | | |
| | Orange | _ | _ | _ | 80704-ORG | _ | | | | |
| 2-Gang | White | 88052 | _ | _ | _ | _ | Non-Magnetic S/S | 84052-40 | _ | - |
| | lvory | 86052 | _ | _ | _ | _ | | | | |
| | Brown | 85052 | _ | _ | _ | _ | | | | |
| • • | | | | | | | | | | |
| | | | | | | | | | | |
| 3-Gang | | | | | | | Non-Magnetic S/S | S73-N | _ | - |
| | | | | | | | | | | |
| | | | | | | | | | | |
| • • • | | | | | | | | | | |

Telephone or Cable Outlet — Box Mounted

| | | Thermoset (Plastic) | | Thermoplastic (Nylon) | Metal | | |
|---------------------------------------|------------|----------------------|----------|-----------------------|------------------|-------------------|--------------------|
| Description | Color | Cat. No. STANDARD | Cat. No. | Cat. No. MIDWAY | Material Type | Cat. No. STANDARD | Cat. No. MIDWAY |
| 1-Gang | White | _ | 80513-W | _ | Aluminum | 83013 | _ |
| Phone/Cable .312" dia. hole | lvory | _ | 80513-I | _ | Brass | 81013 | _ |
| • | Lt. Almond | _ | 80513-T | _ | Polished Brass | 81013-PB | _ |
| 0 | | | | | Stainless Steel | 84013 | _ |
| | | | | | Non-Magnetic S/S | 84013-40 | _ |
| 1-Gang | White | 88013 | _ | PJ11-W* | Non-Magnetic S/S | 84061-40 | _ |
| Phone/Cable .406" dia. hole | lvory | 86013 | _ | PJ11-I* | | | |
| • | Lt. Almond | 78013 | _ | PJ11-T* | | | |
| 0 | Gray | _ | _ | PJ11-GY* | | | |
| <u> </u> | Black | _ | _ | PJ11-E* | | | |
| | Brown | 85013 | _ | PJ11* | | | |
| 1-Gang | White | 88017 | _ | _ | Brass | 81017 | _ |
| Phone/Cable .625" dia. hole | lvory | 86017 | _ | _ | Non-Magnetic S/S | 84017-40 | _ |
| • • | | | | | | | |
| 2-Gang | White | 88062 | _ | _ | Non-Magnetic S/S | 84062-40 | _ |
| Phone/Cable .406" dia. hole | lvory | 86062 | _ | _ | | | |
| • • • • • • • • • • • • • • • • • • • | | | | | | | |

^{*}Adapter piece included, box or strap mounted