



SDX WALL-MOUNT FIBER OPTIC ENCLOSURES

- Self-healing grommet material protects cable and minimizes dust buildup
- Adjustable fiber management rings easily attach to mounting studs
- Ground terminal lug provides grounding option or cable strain relief
- Cutout on side of enclosure allows access to adapter bulkhead when doors are open
- Door options: Split with single lock on service side (optional lock available to install on customer side), solid with or without single lock on customer side
- Constructed of 16-gauge steel, powder-coated black

RECOMMENDED APPLICATIONS:

Telecommunications Room

Equipment Room

SDX WALL-MOUNT ENCLOSURES

DESCRIPTION	MAXIMUM CAPACITY				PART NO.
	FIBERS (USING LC)	ADAPTER PLATES	AND SPLICE TRAYS/ MODULES*	OR MTP® CASSETTES	
Small SDX Enclosure, empty, solid metal door, no lock	48	2	N/A	2	5W110-00N
[A] Small SDX Enclosure, empty, split metal door, one lock and key	48	2	N/A	2	5W120-00N
Small SDX Enclosure, empty, solid metal door, one lock and key	48	2	N/A	2	5W170-00N
Medium SDX Enclosure, empty, solid metal door, no lock	96	4	6 / 4	4	5W310-00N
[B] Medium SDX Enclosure, empty, split metal door, one lock and key	96	4	6 / 4	4	5W320-00N
Medium SDX Enclosure, empty, solid metal door, one lock and key	96	4	6 / 4	4	5W370-00N
[C] Large SDX Enclosure, empty, solid metal door, no lock	288	12	6 / 12	12	5W710-00N
Large SDX Enclosure, empty, split metal door, one lock and key	288	12	6 / 12	12	5W720-00N
Large SDX Enclosure, empty, solid metal door, one lock and key	288	12	6 / 12	12	5W770-00N

ACCESSORIES

DESCRIPTION	PART NO.
SDX Enclosure Lock and Key	5L000-L0K

* = Maximum splice tray capacity is limited by height of selected splice tray. See pages B25-B27 for list of SDX adapter plates and cassettes.