

110-STYLE WIRING BLOCK KITS

	Cat 6A 110-Style Wiring Block, Wall Mount w/legs and C-4 clips*, 64-Pair	41D6A-1F4
	Cat 6 110-Style Wiring Block, Wall Mount w/ Legs 288-Pair, 72 C-4 Clips	41AB6-3F4
	Cat 6 110-Style Wiring Block, Wall Mount w/ Legs, 96-Pair, 24 C-4 Clips	41AB6-1F4
	Cat 6 110-Style Wiring Block, Wall Mount w/o Legs, 96-Pair, 24 C-4 Clips	41NB6-1F4
	Cat 5e 110-Style Wiring Block, Wall Mount w/ Legs, and Clips Kit	41AB2-†F*

	Cat 5e 110-Style Wiring Block, Wall Mount w/ Legs, and ID	41AW2-†00
	Cat 5e 110-Style Wiring Block, Rack-Mount Kit w/ Clips	41DBR-†F*
	Cat 5e 110-Style Wiring Block, Rack Mount	41DR2-†00

† = Number of Pairs: (1) 100, (3) 300 * = Clip Type: (4) C-4, (5) C-5
‡ = Number of Pairs: (1) 100, (2) 200, (3) 300

IT/AV EXTENDER TRANSMITTERS AND RECEIVERS

	HDBaseT™ Extender, Transmitter and Receiver, 100 m	41910-HTE
	HDBaseT Extender, Transmitter and Receiver, 70 m	41910-HT0
	HDBaseT Extender, Receiver only, 70 m	41910-HTR
	HDBaseT Extender IR Emitter and Receiver Kit	41910-HIR
	HDMI® Extender Transmitter and Receiver, 40 m	41910-H00
	VGA Extender with Audio 100m Single Cat Cable Transmitter and Receiver	41910-V01
	USB 1.1 Extender 50m Single Cat Cable Transmitter and Receiver	41910-U11

IT/AV AUDIO AMPLIFIER

	Mixing Audio Amplifier	41920-A01
	Infrared Remote Control Kit	41920-AIR

IT/AV HDMI® CABLES

	High-Speed HDMI Cable with Ethernet	41900-xxE
	HDMI Cable Lock Kit	41900-LKT

xx = Length in feet: (03), (06), (10), (15)

IT/AV QUICKPORT® CONNECTORS

	3.5mm Stereo screw terminal	40839-S~S
	Nickel-Plated F-Type, 3GHz	41084-F*F
	Gold-Plated F-Type, 3GHz	40831-0B*
	RCA to 110	40735-Rx†
	RCA, feedthrough w/black stripe	40830-B*E
	RCA, feedthrough w/red stripe	40830-B*R
	RCA, feedthrough w/yellow stripe	40830-B*Y
	RCA, feedthrough w/green stripe	40830-B~V
	RCA, feedthrough w/blue stripe	40830-B~L
	Snap-in Blank Module	41084-BB*
	HDMI feedthrough QuickPort	40834-00‡
	USB feedthrough QuickPort	40835-00^

* = Color: Ivory (I), White (W), Lt Almond (T), Grey (G), Black (E), Brown (B)
 † = Color: Ivory (I), White (W), Lt Almond (T), Grey (G), Black (E)
 x = Inner Barrel Color: Orange (O), Red (R), White (W), Yellow (Y), Ivory, White connectors also available with Green (V), or Blue (L) Inner Barrel
 * = Color: Ivory (I), White (W), Light Almond (T)
 ~ = Color: Ivory (I), White (W)
 ‡ = Color: Ivory (I), White (W), Lt Almond (T), Black (E)
 ^ = Color: Ivory (I), White (W), Grey (G)

IT/AV MULTIMEDIA OUTLET SYSTEM (MOS)

	FACEPLATE	
	Single-Gang	41290-SM‡
	Dual-Gang	41290-DM‡
	Three-Gang, Stainless Steel	41290-TMS
	DECORA®	
	Decora MOS Converter Strap	41649-00*
	SURFACE-MOUNT BOX	
	Surface-Mount Housing, holds one 1-unit high module, plenum rated	4M089-1*M
	Surface-Mount Box*, 3 unit with Fiber Storage (Not compatible with 41295-VP~†, 41292-DE~ or 41292-AE~)	41296-MM*
	1-UNIT HIGH INSERTS	
	HDMI Feedthrough	41290-HD*
	HD-15 Feedthrough	41293-HD*
	HD-15 Screw terminal	41295-HD*
	2-Port QuickPort Adapter	41291-2Q*
	1-Port QuickPort Adapter	41291-1M*
	Blank	41291-1B*
	RCA Feedthrough composite (Y, W, R)	41292-3R*
	RCA Component Feedthrough (R, G, B)	41292-3D*
	RCA Component Video Module, 110-style termination	41292-DE~
	RCA Composite Video Module, 110-style termination	41292-AE~
	VGA PC Module, 110-style termination†	41295-VP•
	VGA Monitor Module, 110-Style termination†	41295-VM•
	1.5-UNIT HIGH INSERTS	
	2-Port QuickPort Adapter, 45° exit	41294-2Q*
	Passthrough Module (1.5-units high)	41297-2P*
	speakON® Connector, 4-pole, screw terminal^	41297-SP4
	XLR Connector, 3-pole, screw terminal^	41297-XL3

‡ = Color: Ivory (I), White (W), Grey (G), Black (E), Light Almond (T), Stainless (S)
 * = Color: Ivory (I), White (W), Grey (G), Black (E), Light Almond (T)
 • = Color: Ivory (I), White (W) ~ = Color: Ivory (I), White (W), Light Almond (T)
 † = Must be Used in PC / Monitor Pairs
 ^ = Must be installed in 1.5-unit high MOS Passthrough Module (41297-2P*)
 For fiber adapters see page 8