

Hazardous Location Conduit Systems

Enlargers, Reducers and Thread Converters

Connector DescriptionEXS - Stainless Steel 316
IP Rating
IP66

Approvals

- Approved to Exe II and Exd IIc, Groups 1 and 2, Zones 1, 2, 21, 22
- ATEX Certification: BASEEFA 07 ATEX 0247X
- IECEx Certification: IECEx BAS07.0090X
- Approved to Class I Div. 1 ABCD Class II Div. 1 EFG (does not include M16 and 3/4" NPT)
- UL® 1203
- CSA C22.2 No. 60079-04, C22.2 No. 60079-1









			Intertek —
M40	M50	M63	M75
	inco		
EXS/M25-M40/E			
EXS/M32-M40/E	EXS/M32-M50/E		
ENO/MOZ MHO/E	EXS/M40-M50/E	EXS/M40-M63/E	
EXS/M50-M40/R	ENO/INITO INIOO/E	EXS/M50-M63/E	EXS/M50-M75/E
EXS/M63-M40/R	EXS/M63-M50/R	E/G/MOO MOO/E	EXS/M63-M75/E
EXS/M75-M40/R	EXS/M75-M50/R	EXS/M75-M63/R	Elo/Moo Mi o/E
DIGHT O HI TO/IT	ZAGAMI O MOGAT	Dio/iii/ 0 Moo/it	
EXS/PG29-M40/TC			
EXS/PG36-M40/TC	EXS/PG36-M50/TC		
EXS/PG42-M40/TC	EXS/PG42-M50/TC	EXS/PG42-M63/TC	
EXS/PG48-M40/TC	EXS/PG48-M50/TC	EXS/PG48-M63/TC	
EXS/100-M40/TC			
EXS/125-M40/TC	EXS/125-M50/TC		
EXS/150-M40/TC	EXS/150-M50/TC	EXS/150-M63/TC	
EXS/200-M40/TC	EXS/200-M50/TC	EXS/200-M63/TC	
EXS/250-M40/R	EXS/250-M50/R		
EXS/300-M40/R	EXS/300-M50/R		EXS/300-M75/R



United States

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services
Tel: 888.862.3289





Hazardous Location Conduit Systems











EXS/200-PG36/TC

EXS/200-PG29/TC



EXS/200-PG48/TC

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354

EXS/200-PG42/TC



