


Hardware and Rough-In Products

Machine Bolts

- Steel, zinc plated
- Accurate, uniform threads
- Round heads standard; flat heads available in some sizes



| CAT. NO. ROUND HEAD | CAT. NO. FLAT HEAD | SIZE | STD. CTN. |
|------------------------|-----------------------|-----------------|--------------|
| 54-521 | 54-621 | 6-32 x 1/2" | 1,000 |
| 54-522 | 54-622 | 6-32 x 3/4" | 1,000 |
| 54-523 | 54-623 | 6-32 x 1" | 1,000 |
| 54-524 | 54-624 | 6-32 x 1 1/4" | 1,000 |
| 54-525 | 54-625H | 6-32 x 1 1/2" | 1,000 |
| 54-526 | 54-626 | 6-32 x 2" | 1,000 |
| 54-527 | 54-627 | 6-32 x 2 1/2" | 1,000 |
| 54-541P | | 8-32 x 1/2" | 1,000 |
| 54-542P | 54-642 | 8-32 x 3/4" | 1,000 |
| 54-543P | 54-643 | 8-32 x 1" | 1,000 |
| 54-544 | | 8-32 x 1 1/4" | 1,000 |
| 54-545P | 54-645H | 8-32 x 1 1/2" | 1,000 |
| 54-546P | 54-646 | 8-32 x 2" | 1,000 |
| 54-547 | | 8-32 x 2 1/2" | 500 |
| 54-548 | | 8-32 x 3" | 500 |
| 54-551 | | 10-24 x 1/2" | 1,000 |
| 54-552 | | 10-24 x 3/4" | 1,000 |
| 54-553 | | 10-24 x 1" | 1,000 |
| 54-554 | | 10-24 x 1 1/4" | 1,000 |
| 54-555 | | 10-24 x 1 1/2" | 1,000 |
| 54-556 | | 10-24 x 2" | 500 |
| 54-561 | | 10-32 x 1/2" | 1,000 |
| 54-562 | | 10-32 x 3/4" | 1,000 |
| 54-563P | | 10-32 x 1" | 1,000 |
| 54-564 | | 10-32 x 1 1/4" | 1,000 |
| 54-565 | | 10-32 x 1 1/2" | 1,000 |
| 54-566 | | 10-32 x 2" | 500 |
| 54-570P | | 1/4-20 x 3/8" | 1,000 |
| 54-571P | | 1/4-20 x 1/2" | 1,000 |
| 54-572P | | 1/4-20 x 3/4" | 500 |
| 54-573P | | 1/4-20 x 1" | 500 |
| 54-574 | | 1/4-20 x 1 1/4" | 500 |
| 54-575 | | 1/4-20 x 1 1/2" | 1,000 |
| 54-576 | | 1/4-20 x 2" | 500 |
| 54-577 | | 1/4-20 x 2 1/2" | 250 |
| 54-578 | | 1/4-20 x 3" | 250 |

Hexagon Nuts

- For use with machine bolts
- Finest quality steel, zinc plated



| CAT. NO. | SIZE | STD. CTN. |
|----------|---------|--------------|
| 55-004P | 6-32 | 1,000 |
| 55-005P | 8-32 | 1,000 |
| 55-006P | 10-24 | 1,000 |
| 55-007P | 10-32 | 1,000 |
| 55-008P | 1/4-20 | 1,000 |
| 55-010 | 5/16-18 | 1,000 |
| 55-012 | 3/8-16 | 1,000 |

Self-Piercing Screws

- For fastening to sheet metal up to .040 (25 gauge)
- Eliminates pre-drilled holes
- 1/4" Hex Washer head, slotted; fits 54-090 Magnetic Driver



| CAT. NO. | SIZE | STD. CTN. |
|----------|-------------|--------------|
| 54-001 | 7 x 1/2" | 1,000 |
| 54-002 | 8 x 1/2" | 1,000 |
| 54-003 | 8 x 3/4" | 1,000 |
| 54-004P | 10 x 1/2" | 1,000 |
| 54-005P | 10 x 3/4" | 1,000 |
| 54-006P | 10 x 1" | 1,000 |
| 54-007P | 10 x 1 1/4" | 1,000 |
| 54-008P | 10 x 1 1/2" | 1,000 |
| 54-009P | 10 x 2" | 1,000 |

Self-Drilling Screws

- Drill their own hole and form mating threads
- #8 screws fasten combined material thickness up to 3/32"
- #10 screws fasten combined material thickness up to 1/4"
- Hex Washer Head (no slot)
- 1/4" hex head fits 54-090 Magnetic Driver
- 5/16" hex head fits 54-091 Magnetic Driver



| CAT. NO. | SIZE | HEAD SIZE (IN.) | POINT NO. | STD. CTN. |
|----------|--------------|--------------------|--------------|--------------|
| 54-300P | 8 x 1/2" | 1/4 | 2 | 1,000 |
| 54-301 | 8 x 3/4" | 1/4 | 2 | 1,000 |
| 54-302P | 10 x 5/8" | 5/16 | 3 | 1,000 |
| 54-303P | 10 x 1" | 5/16 | 3 | 1,000 |
| 54-304 | 12-14 x 3/4" | 5/16 | 3 | 1,000 |

Magnetic Drivers

- For driving self-piercing and self-drilling hex head screws
- Fits power screwdriver and electric drill chucks
- Strong permanent magnet holds screw in position



| CAT. NO. | SIZE | STD. CTN. |
|----------|---|--------------|
| 54-091 | 5/16" x 1 1/8" Hex-Head Magnetic Driver | 12 |
| 54-090 | 1/4" x 1 1/8" Hex-Head Magnetic Driver | 12 |