

Pos-E-Kon®

A Series 16 Amps 600 VAC



3 or 4 Contacts + Ground: 10A
 10, 16 & 32 Contacts + Ground: 16A

Install to Matching Series Hood/Base



3 or 4 (600V)	10	16	32
---------------	----	----	----



Screw Terminal Inserts

SCREW TERMINAL INSERTS	3 OR 4 + G	10 + G	16 + G	32 + G
 <p>MALE – PINS 20-14 AWG (0.5-2.5 mm²)</p>	MS203A or MS204A (16 AWG max)	MS210A	MS216A	MS216A+ MS232A
 <p>FEMALE – SLEEVES 20-14 AWG (0.5-2.5 mm²)</p>	FS103A or FS104A (16 AWG max)	FS110A	FS116A	FS116A+ FS132A

Crimp Terminal Inserts

CRIMP TERMINAL INSERTS	—	10 + G	16 + G	32 + G
 <p>MALE INSERT (Order contacts below)</p>	—	MC410A	MC416A	MC416A+ MC432A
 <p>FEMALE INSERT (Order contacts below)</p>	—	FC310A	FC316A	FC316A+ FC332A



Use small blade screwdriver to push wire entry tab in for easy contact removal.






Crimp Tool

CAT. NO.

WT611TB



Contacts Selection

CRIMP CONTACTS	WIRE AWG (MM ²)	IDENTIFICATION
	20 AWG (0.5 mm ²)	No Groove
	18 AWG (0.75-1 mm ²)	1 Groove
	16 AWG (1.5 mm ²)	2 Grooves
	14 AWG (2.5 mm ²)	3 Grooves
	12 AWG (4.0 mm ²)	No Groove

For all Crimp Terminal "A" Inserts:

FEMALE	MALE
FP2000	MP2000
FP1800	MP1800
FP1600	MP1600
FP1400	MP1400
FP1200	MP1200

Pos-E-Kon® Pin and Sleeve Connectors