

# Pos-E-Kon™

## M (3P Coax) Series 1.5 Amps 50 VAC



### Specifications

<b>Number of Poles</b>	3
<b>Termination Method</b>	Crimp (or solder)
<b>Contacts</b>	Solid Drilled, 3.6mm CoAxial Copper Alloy, Gold Plated
<b>Rated Current</b>	1.5A
<b>Rated Voltage</b>	50V
<b>Volume Resistance</b>	≤6 milliohms
<b>Surge Impedance</b>	50 Ohms
<b>Frequency Range</b>	2 GHz

### Inserts

Coax Pin & Sleeve


3 Positions


Crimp Terminal Inserts		3P CoAx
	Male Insert	MC303M
	Female Insert	FC203M



Pos-E-Kon™

### Contacts

Tools		
	Crimping Tool	<b>CT700TB</b>
	RG174, 179, 316 Crimp Die RG58 Crimp Die	<b>CD710TB</b> <b>CD720TB</b>
	Contact Removal Tool	<b>RT000TB</b>
	Insert Puller	<b>PT300TB</b>

Male Crimp Contacts		
	Male Coax Pin Contact	<b>MCX500</b>
	Cable Size/Type	RG-174 RG-179 RG-316
	Male Coax Pin Cotact	<b>MCX510</b>
	Cable Size/Type	RG-58

Female Crimp Contacts		
	Female Coax Pin Contact	<b>FCX400</b>
	Cable Size/Type	RG-174 RG-179 RG-316
	Female Coax Pin Cotact	<b>FCX410</b>
	Cable Size/Type	RG-58

Dummy Inserts		0
	Male Blind Insert: for place keeping in Insert Holder	<b>MC100M</b>
	Female Blind Insert: for place keeping in Insert Holder	<b>FC000M</b>