

Production on Site

Specifications

General

The MTX-MK3 printer is a high resolution high speed production thermo transfer printer for both monochrome and color printout. Loaded with a number of cards in a feeder magazine the printer feeds the cards one by one through the printer, where all the individually tags are printed row by row. The ready printed cards are automatically fed to an output magazine. The printer is controlled by WinSign (WSG-NG-INCL) software. Different marking file formats can be imported.

System Layout

The X-Card system comprises of the MTX-MK3 printer, software winSign and marker tag cards type PFC for cable, wire and component marking. Some PFC cards are used together with Partex holder system PTPLUS, PTZPLUS, PTC, PM10, PM20, PM24 and PS20T. Other cards are used for direct marking and are attached with Ty-Rap[®] cable ties.

Thermo Transfer	
300 dpi Resolution	
Printing Speed	
4 seconds per card for resin bla 25 seconds per card four full co	ack ink.
Software	
WinSign-NG-INCL	
Communication Interface	
USB 1.1 cable included	
Power Connection	
110 VAC-240 VAC, 50 – 60 Hz. FCC Class B, CE, UL and CUL	
Measurements	
(L x W x H): 462x239x256mm	
Weight	
7 kg	
Temperature Range	
Operating temperature range: Operating humidity: Storage temperature:	


www.tnb.ca



E-Z-Code[®]




Applications



Product and ordering information

Cat. No.	Description	Contents		
МТХ-МКЗ	MTX-MK3 Thermal Printer type P330	Printer + WinSign + USB Cable		
MTX-MK3-USB	MTX-MK3 Interface Printer Cable			
MTX-MK3-CLEANKIT	Cleaning Kit for MTX-MK3-P330	Swab + Cleaning Cards + Rollers		
MTX-MK3-CR	Cleaning Roller for MTX-MK3-MC	To Remove Dust from the Card Before Printing		
MTX-MK3-F301E	Printer Ribbon F301 Black			
MTX-MK3-RC330	Printer Ribbon RC330 Color			



- The MTX-MK3-P330 system contains several different card types that covers the need for cable, wire and component markers.
- With the MTX-MK3-P330 it is now possible to print in color. This is can only be done if you have the latest version of WinSign.

Product and ordering information

Cat. No.	Description	Marker Tag Length x Height mm (in)	Marker Tags per Card	Marker Tags per Box	Material	Suitable Partex Holder System
PFC04212KAØ		12 x 4.2		525	ABS	PTPLUS type (refer to page 119)
PFC04215KAØ	Morker Teg Wire	15 x 4.2	21			
PFC04218KAØ	Marker Tag – Wire	18 x 4.2	21			
PFC04221KAØ		21 x 4.2	1			
PFC07533KAØ	Marker Tag – Cable	33 x 7.5	9	225		PM type (refer to page 117)
PFC09518KAØ	Marker Tag – Component / Cable	18 x 9.5	20	500		
PFC09540KAØ	Marker Tag Cable Marking	40 x 9.5	8	200	Delvomid / DA11	Cable ties (refer to page 97)
PFC09580KAØ	Marker Tag – Cable Marking	80 x 9.5	4	100	Polyamid / PA11	

Ø = Card Color, 4 = Yellow, 9 = White