



## Ball-Lock Type

The Ball-Lock Type stainless steel ties from Thomas & Betts are self-locking, requiring no time consuming crimping or folding operations.

- Strong self-locking mechanism (steel ball), with low insertion force
- Fast, easy and reliable installation
- 2 grades of non-magnetic stainless steel: 304 grade for standard applications and 316 (marine grade) for extra corrosion resistance



### Ball-Lock Type: uncoated

PRODUCT REF. STAINLESS STEEL 304	PRODUCT REF. STAINLESS STEEL 316	LENGTH X WIDTH [mm]	MAX. BUNDLE DIAMETER [mm]	MIN. TENSILE STRENGTH [N]
YLS-4.6-100A	YLS-4.6-100B	100 x 4.6	20	440
YLS-4.6-125A	YLS-4.6-125B	125 x 4.6	22	440
YLS-4.6-150A	YLS-4.6-150B	150 x 4.6	24	440
YLS-4.6-200A	YLS-4.6-200B	200 x 4.6	50	440
YLS-4.6-300A	YLS-4.6-300B	300 x 4.6	80	440
YLS-4.6-360A	YLS-4.6-360B	360 x 4.6	100	440
YLS-4.6-520A	YLS-4.6-520B	520 x 4.6	150	440
YLS-4.6-680A	YLS-4.6-680B	680 x 4.6	200	440
YLS-4.6-840A	YLS-4.6-840B	840 x 4.6	250	440
YLS-4.6-1000A	YLS-4.6-1000B	1000 x 4.6	300	440
YLS-4.6-1200A	YLS-4.6-1200B	1200 x 4.6	365	440
YLS-4.6-1400A	YLS-4.6-1400B	1400 x 4.6	425	440
YLS-7.9-100A	YLS-7.9-100B	100 x 7.9	20	1110
YLS-7.9-125A	YLS-7.9-125B	125 x 7.9	22	1110
YLS-7.9-150A	YLS-7.9-150B	150 x 7.9	24	1110
YLS-7.9-200A	YLS-7.9-200B	200 x 7.9	50	1110
YLS-7.9-300A	YLS-7.9-300B	300 x 7.9	80	1110
YLS-7.9-360A	YLS-7.9-360B	360 x 7.9	100	1110
YLS-7.9-520A	YLS-7.9-520B	520 x 7.9	150	1110
YLS-7.9-680A	YLS-7.9-680B	680 x 7.9	200	1110
YLS-7.9-840A	YLS-7.9-840B	840 x 7.9	250	1110
YLS-7.9-1000A	YLS-7.9-1000B	1000 x 7.9	300	1110
YLS-7.9-1200A	YLS-7.9-1200B	1200 x 7.9	365	1110
YLS-7.9-1400A	YLS-7.9-1400B	1400 x 7.9	425	1110

### Ball-Lock Type: coated

PRODUCT REF. STAINLESS STEEL 316 POLYESTER COATED	LENGTH X WIDTH [mm]	MAX. BUNDLE DIAMETER [mm]	MIN. TENSILE STRENGTH [N]
YLS-4.6-100BC	100 x 4.6	20	440
YLS-4.6-125BC	125 x 4.6	22	440
YLS-4.6-150BC	150 x 4.6	24	440
YLS-4.6-200BC	200 x 4.6	50	440
YLS-4.6-300BC	300 x 4.6	80	440
YLS-4.6-360BC	360 x 4.6	100	440
YLS-4.6-520BC	520 x 4.6	150	440
YLS-4.6-680BC	680 x 4.6	200	440
YLS-4.6-840BC	840 x 4.6	250	440
YLS-4.6-1000BC	1000 x 4.6	300	440
YLS-4.6-1200BC	1200 x 4.6	365	440
YLS-4.6-1400BC	1400 x 4.6	425	440
YLS-7.9-100BC	100 x 7.9	20	530
YLS-7.9-125BC	125 x 7.9	22	530
YLS-7.9-150BC	150 x 7.9	24	530
YLS-7.9-200BC	200 x 7.9	50	530
YLS-7.9-300BC	300 x 7.9	80	530
YLS-7.9-360BC	360 x 7.9	100	530
YLS-7.9-520BC	520 x 7.9	150	530
YLS-7.9-680BC	680 x 7.9	200	530
YLS-7.9-840BC	840 x 7.9	250	530
YLS-7.9-1000BC	1000 x 7.9	300	530
YLS-7.9-1200BC	1200 x 7.9	365	530
YLS-7.9-1400BC	1400 x 7.9	425	530

## Application tools

### Product Ref. CT3

- Tensioning and manual cutting hand tool
- For Ball-Lock Type and Ladder Type ties, coated and uncoated

### Product Ref. CT5 and CT6

- Adjustable tension setting, automatic cutting hand tool
- CT5: for Ladder Type ties, coated and uncoated
- CT6: for Ball-Lock Type ties, coated and uncoated



CT3