

Copper H-Tap Connectors for Copper Conductors

Copper H-Taps – Certified to 600 V 90°C Applications

- H-type compression taps
- For aluminum-to-aluminum, aluminum-to-copper and copper-to-copper stranded-conductor applications
- Concentric and compact code strandings

Exclusive FILLERLOK tab design.

Material: High-Conductivity
Wrought Aluminum



Cat. No.	Combinations			Length (in.)	Die Code Cat. No.				Colour Code
	Main	Branch	Side Tap		TBM6-TBM6S TBM6ORS	Hydraulic TBM14M 13100A	TBM12 12-TON HEAD	TBM15I 15-TON HEAD	
63105†	2-6	8-14	-	3/4	13474 upper 13477 lower	15530	TBM12D-4	15530*	Orange
63110	4-6	4-6		1-1/2	13470	15501A	TBM12D-H	15001A*	Green
63118	2/0-2	8-14		3/4					
63125	2/0-2	1/0-6		1-1/2					
63140	4/0-2/0	2-10		8-14	3	13471	15502	15502*	Blue
63148•	4/0-2/0	3/0-1						15502	
63160	500-4/0	4/0-2		2-6	2-3/4	-	-	-	15612
63169	750-4/0	750-4/0	-	3					
63170	1000-500	1000-1/0	-	6					
63180	750-350	350-1/0	1-6	3			15620	Black	

* Use with adaptor Cat.No.15500-TB.

† 63105 also installed by TBM5/TBM5S with 13455 die or TBM8/TBM8S with 13462 die.

• 63148 – #1 CU or AL - wire bent double (hairpin).

For Smart™ Tools Installation

63110,63118,63125: Use TBM8-750HG

63140,63148:Use TBM8-750BH

Tooling: pp. E4-E62

Die Selector Chart: pp. E35-E50