

## Fittings and Brackets

### 90° Fittings


#### AB284R

AB284RHDG

AB284REG

AB284R

Wt./C 230 lb.




#### AB284L

AB284LHDG

AB284LEG

AB284L

Wt./C 230 lb.




#### AB299

AB299HDG

AB299EG

AB299

Wt./C 40 lb.




#### X201

X201HDG

X201EG

X201

Wt./C 65 lb.




#### X204

X204HDG

X204EG

X204

Wt./C 1-90 lb.




#### X289

X289HDGC

X289EG

X289

Wt./C 105 lb.



#### X299

X299HDGC

X299EG

X299

Wt./C 38 lb.



#### N205


N205HDGC

N205EG

N205

N205SS6C

Wt./C 74 lb.



#### N219


N219HDG

N219EG

N219

N219SS6

Wt./C 71 lb.



**Standard Dimensions**

Hole Spacing  
Hole Spacing  
Hole Size  
Material  
Material

13/16 in. From End  
1-7/8 in. Centers  
9/16 in. Diam.  
1-5/8 in. Width  
1/4 in. Thick

**Materials**

HDG(C)  
EG(C)  
(No suffix)  
SS6(C)

Hot-Dipped Galvanized  
ElectroGalvanized  
GoldGalv®  
Stainless Steel 316