

## Finishes and Materials

### Finishes on Steel

#### Bare (Suffix BC)

#### Pregalvanized (Suffix PGC)

A zinc coating is applied to the steel coil at the mill prior to fabrication. Once the material is worked by roll-forming, cutting, or punching, minimal protection is provided for raw edges. This weakness is typical with precoated material and affects the channel section around holes, extreme ends, and the edges of the U-shape lips. Superstrut® pregalvanized material is in conformance with ASTM A-525/G-90 specification standards, representing 0.90 oz. of zinc per square foot of steel. This finish is often referred to as “mill galvanized.”

#### Electrogalvanized (Suffix EGC)

Often referred to as “zinc plated” or “electroplated zinc,” the steel and 0.5 mils of zinc are bonded by an electrolysis process. Electrogalvanizing is most commonly applied to small fittings, hardware, and threaded products.

#### GoldGalv® (No Suffix)

Gold coloured zinc dichromate is applied over the zinc, producing a chemically bonded non porous barrier for protection from moisture and air. This extends the protective life of the zinc, and provides an excellent base for paint, if desired. The GoldGalv® hardware finish also provides a low electrical resistance when grounding of the system is required. Superstrut® channel and fittings are plated after fabrication, so there are no unprotected edges from cutting or punching. Where field cutting is necessary or scratches occur due to construction handling, you still have the sacrificial protection of the plated zinc to minimize the corrosion of raw edges and prevent spreading.

#### Hot-Dipped Galvanized (Suffix HDGC)

The material is zinc coated after fabrication providing total product protection on all surfaces. The fabricated channel or fitting is suspended and then dipped into tanks of hot zinc for a prolonged period, creating a coherent bond. The result is superior corrosion resistance as compared to pregalvanized material. Hot-dipped galvanizing is not recommended for threaded products, considering the zinc coating thickness will often disrupt the threads. Superstrut® hot-dipped galvanized is in conformance with ASTM Specifications A-123 (formerly A-386) and A-153. Superstrut channels maintain a minimum 1.5 oz. of zinc per square foot of steel or 2.5 mils (ASTM A-123, Thickness Grade 65). This finish is also referred to as “Hot-dipped galvanized after fabrication”.

#### Epoxy Powder Coated — Green, Grey or White (Suffix GR, GY or WH)

Epoxy powder resins are applied electrostatically to the steel after fabrication. Once the material is completely covered with the powder-form epoxy, it proceeds through a 400°F (204°C) baking process for ten minutes, creating a chemical bond. This results in a minimum of 1.5 mil thickness of epoxy coating providing excellent resistance to chipping or peeling.

### Special Materials

#### Aluminum (Suffix ALC)

Superstrut® channel is available in aluminum. Fittings in HDG finish or fiberglass material are suggested for fastening products.

#### Stainless Steel (Suffix SS)

Superstrut® channel is supplied in Type 316 (T316L) stainless steel. All fittings and accessories are in 316SS (SS6). Contact your Regional Sales Office for availability.

**Thomas & Betts reserves the right to change material and finish specifications without notice, to improve its products.**

Bare (suffix BC) is available upon request.

## Surface Raceway and Lighting Systems

### Fixture Fittings

#### AB844PGC


Steel Closure Strip

#### AB844PC

Plastic Closure Strip Colour: Gold

#### AB844PCGY


Plastic Closure Strip Colour: Grey



- When used as a raceway, channel is normally installed with the slot up. After wiring has been completed the closure strip is installed.
- For all channels
- Standard length: 10 ft.

#### AB803

Cast Conduit Connector




To connect 1/2 in. or 3/4 in. conduit to raceway channel. Furnished complete with stud nuts and hex nuts. Part has removable bushing to increase size from 1/2 in. to 3/4 in.

Wt./C 60 lb.

#### AB815

Swing Connector




Nuts and bolts to clamp to channel is included. For 1/2 in. or 3/4 in. conduit.

Wt./C 95 lb.

#### AB885


15° Swivel



Nuts and bolts to clamp to channel included. For 1/2 in. or 3/4 in. conduit.

Wt./C 25 lb.

#### AB867 Spacer




For use with AB866 wiring stud nuts.

Wt./C 24 lb.

#### AB866


Wiring Stud Nut




1/2 in. Pipe thread

Wt./C 21 lb.

#### 811 Stud Nut





#### 812 Stud Nut



For attaching fixture to slot down channel or to slot up knockouts. Specify length. Hex nut included.

#### AB868

Fiber Retainer for Cables Until Closure Strip is Installed



Wt./C 3 lb.

STD. PACK: 100

| Cat. No. | For Channel | Wt./C lb. |
|----------|-------------|-----------|
| 811-1STR | 1/4 x 1     | 8         |
| 811-2STR | 1/4 x 1-1/4 | 9         |

| Cat. No. | For Channel | Wt./C lb. |
|----------|-------------|-----------|
| 812-1EG  | 1/4 x 1     | 6         |