

Mounting Bases, Cable Ties and Accessories

Saddle Support Base


This mounting base provides a saddle for the wire run. Ty-Rap^{\otimes} tie is threaded under bundle and tied in usual manner. **Note:** For additional materials, see Technical Services.



TC5142

10

۹ľ



| STD. PKG. Cat. No. | BULK PKG. CAT. NO. | MOUNTING METHOD | MAXIMUM TIE WIDTH ACCOM. | WIDTH IN./MM | LENGTH IN./MM | STD. PKG. QTY. | BULK PKG. QTY. | | |
|------------------------------------------------------------|-----------------------|--------------------|--------------------------------|--------------------------------------------------|------------------|-------------------|-------------------|--|--|
| _ | TC140 | #4 Pan Head | .091 | .344/8.74 | .563/14.30 | — | 500 | | |
| TC5141 | TC141*† | #6 Pan Head | .190 | .439/11.15 | .672/17.07 | 100 | 500 | | |
| TC5142 | TC142 ⁺ | #10 Pan Head | .301 | .563/14.30 | .922/23.42 | 100 | 500 | | |
| * Add suffix FR for flame-retardant material (TC141 only). | | | | [†] Add suffix X for UV Black material. | | | | | |

TC5141

10

-

-


1

Natural nylon color.

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

Multiple-Bundle Mounting Strips

These nylon mounting strips for parallel installation of wire bundles can accommodate up to six closely spaced bundles.



| STD. PKG. Cat. No. | MAXIMUM Mounting Method | TIE WIDTH Accom. | WIDTH IN./MM | LENGTH IN./MM | CAPACITY (BUNDLES) | MIL. STD. Part no. | BULK PKG. QTY. | |
|-----------------------|-------------------------------|---------------------|-----------------|------------------|-----------------------|-----------------------|-------------------|--|
| TC1101 | #6 Screws | .190 | .50/12.70 | 1.75/44.45 | 1 | MS3339-1 | 100 | |
| TC1102 | #6 Screws | .190 | .50/12.70 | 3.00/76.20 | 2 | MS3339-2 | 100 | |
| TC1103 | #6 Screws | .190 | .50/12.70 | 4.25/107.95 | 3 | MS3339-3 | 100 | |
| TC1104 | #6 Screws | .190 | .50/12.70 | 5.50/139.70 | 4 | MS3339-4 | 100 | |
| TC1105 | #6 Screws | .190 | .50/12.70 | 6.75/171.45 | 5 | MS3339-5 | 100 | |
| TC1112 | #6 Screws | .301 | .63/15.88 | 9.60/243.84 | 6 | MS3339-11 | 100 | |
| TC1113 | #6 Screws | .301 | .63/15.88 | 2.10/53.34 | 1 | MS3339-6 | 100 | |
| TC1114 | #6 Screws | .301 | .63/15.88 | 3.60/91.44 | 2 | MS3339-7 | 100 | |
| TC1115 | #6 Screws | .301 | .63/15.88 | 5.10/129.54 | 3 | MS3339-8 | 100 | |
| TC1116 | #6 Screws | .301 | .63/15.88 | 6.60/167.64 | 4 | MS3339-9 | 100 | |
| TC1117 | #6 Screws | .301 | .63/15.88 | 8.10/205.74 | 5 | MS3339-10 | 100 | |
| Natural nylon | color | | | | | | | |

Natural nylon color.

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

Provides a mounting range for bundles from $\frac{1}{4}$ " through 4" in diameter!

Single-Bundle Mounting Base



| | | | | | | | 74 |
|-----------------------|-----------------------|--------------------|---------------------------------------|-----------------|------------------|-------------------|-------------------|
| STD. PKG. Cat. No. | BULK PKG. Cat. No. | MOUNTING METHOD | MAXIMUM TIE WIDTH ACCOM. IN./MM | WIDTH IN./MM | LENGTH IN./MM | STD. PKG. QTY. | BULK PKG. QTY. |
| _ | TC101 | #10 Screws | .190/4.83 | .500/12.7 | 2.00/50.80 | _ | 1,000 |
| TC503 | TC103 | 1/4" Screws | .301/7.65 | .625/15.88 | 3.08/78.23 | 100 | 500 |
| The TOTOT | 1 70400 1 1 | 11 | | | | | |

The TC101 and TC103 nylon bases provide a mounting range for bundles from ¼" through 4" in diameter. One mounting hole is slotted to permit adjustment of the bundle position up to the time of actual bundle installation.

• Natural nylon color.

For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).



United States Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services Tel: 888.862.3289

