## Mounting Bases, Cable Ties and Accessories

## A fast and simple harnessing method for neat, versatile wire management.

## **Stud Mounting System**

- Great for harnessing wires, cables and hoses to truck and trailer chassis
- Fast, easy installation, using standard ¾" power drill and application tool or simply hammer on
- Unlimited harnessing flexibility using conventional T&B cable ties
- Custom drill bit quickly installs base to proper torque won't crack or break mounting base due to being overtightened
- Unique 4-way multi-directional design
- 10-position harness capability
- Available for ¾", ½", ¾", and ¾" stud/bolt sizes
- Self-tapping thread design for reliable installation onto stud
- High pull-out strength of 500+ lbs.

Thomas & Betts Stud Mount Fastening System is a fast and simple harnessing method for neat, versatile, cord, cable, hose, and wire management. Using a custom drill bit for your ¾" power drill, the Stud Mount base is quickly attached onto a threaded stud or bolt to the proper torque—every time. The innovative "X" design of the base reliably supports many types of cable or hose assemblies using a wide range of conventional T&B cable ties. Designed with 10 separate lashing positions, the Stud Mount offers unlimited wire harnessing arrangements. T&B's Stud Mount is available in four convenient stud bolt sizes.



The Stud Mount Cable Fastening System includes a range of bases and the custom drill bit that mounts all sizes.



During installation, the custom Stud Mount drill bit application tool ejects itself from mounting base, ensuring proper torque and preventing cracking or breaking of the mount from being overtightened.



Virtually unlimited harnessing flexibility is provided in the unique 10-position harness design of the Stud Mount base.

BULK PKG. Cat. No.	DESCRIPTION	STUD SIZE	MATERIAL	COLOR	BULK PKG.
XMNY-375-0-D	Mount Fastener	3/8	Nylon, UV Stabilized	Black	500
XMNY-500-0-D	Mount Fastener	1/2	Nylon, UV Stabilized	Black	500
XMNY-625-0-D	Mount Fastener	5/8	Nylon, UV Stabilized	Black	500
XMNY-750-0-D	Mount Fastener	3/4	Nylon, UV Stabilized	Black	500
WTXM	Application Tool	_	Tool Steel	_	1

Material: Impact-resistant weatherable black nylon
For use in temperatures ranging from -40° F to 185° F (-40° C to 85° C).

