
## Ty-Rap® High-Performance Stainless Steel Cable Ties


## Ties to use and re-use with quickness and ease! Ty-Rap® Re-Usable Stainless Steel Cable Ties

- 200/300 series stainless steel construction
- Fully coated in non-toxic, halogen-free low-smoke Nylon 11 for extra corrosion resistance
- Unique buckle design for easy application and re-use
- May be double-wrapped for additional tensile strength
- Also available in 316 grade stainless steel (to order, add -316 suffix to catalog number)







Insert cable tie tail through holding tabs and locking emboss



Bend cable tie tail up



Insert cable tie tail back through holding tabs, creating as tight a bend as possible



For increased tensile strength follow steps #4 and #5 
\*Patent Pending

Bend cable tie tail up

Fold cable tie tail over holding tabs

CAT. NO.	TENSILE STRENGTH (LBS/N)	WIDTH (IN/MM)	LENGTH (IN/MM)	WEIGHT (LBS/KG)	STD. PKG. QTY.
SSR6-250C	75/333.60	.25/6.35	6/152	1.4/.64	100
SSR9-250C	75/333.60	.25/6.35	9/229	1.8/.82	100
SSR12-250C	75/333.60	.25/6.35	12/305	2.1/.95	100
SSR18-250C	75/333.60	.25/6.35	18/457	3.0/1.36	100
SSR24-250C	75/333.60	.25/6.35	24/610	3.7/1.68	100
SSR6-375C	100/444.80	.38/9.53	6/152	1.8/.82	100
SSR9-375C	100/444.80	.38/9.53	9/229	2.0/.91	100
SSR12-375C	100/444.80	.38/9.53	12/305	3.1/1.41	100
SSR18-375C	100/444.80	.38/9.53	18/457	4.4/2.00	100
SSR24-375C	100/444.80	.38/9.53	24/610	6.6/2.99	100
SSR30-375C	100/444.80	.38/9.53	30/762	7.0/3.18	100
SSR36-375C	100/444.80	.38/9.53	36/914	8.3/3.76	100

Material: 200/300 Series Stainless Steel

.015" (.38mm) metal thickness; .045" (1.1mm) coated thickness

Note: This product may be double-wrapped for additional tensile strength.

For additional colors and uncoated ties, consult Thomas & Betts Customer Service for pricing and availability.

For 316 Stainless Steel, add suffix -316 after catalog number. Consult Customer Service for availability.

