## **Ty-Rap**°

### Ty-Rap<sup>®</sup> Installation Tools

Lightweight. Economical. Durable. Perfect for spot-tying!

#### Ty-Rap<sup>®</sup> Cable Tie Installation Tool — Light Duty

- Installs Ty-Rap cable ties up to .301" wide by .080" thick
- Designed for use by both left- and right-handed operators
- Lightweight, high-impact polymer and steel components

They cinch up the tie with a squeeze action, and cut away the excess tail when twisted  $180^{\circ}$ . A specially designed pawl cuts away the tail if the tension limit is exceeded, thereby preventing the cable tie from being over-tightened.

### Cuts tail off — flush.

#### Ty-Rap<sup>®</sup> Cable Ties Installation Tool — Metallic

- Installs Ty-Rap<sup>®</sup> cable ties
- Rugged metallic construction
- · Pistol-grip installation tool
- · Easy tension adjustment
- Tensions and cuts tie tail off flush



STD. PKG. Cat. No.	DESCRIPTION	TIE BODY WIDTH IN./MM	STD. PKG. QTY.
WT1-TB	Cable Tie Installation Tool, 18–50 lbs. (80–222.4N)	.09–.18/2.39–4.67	1
WT2-TB	Cable Tie Installation Tool, 50–120 lbs. (222.4–533.8N)	.18–.301/4.67–7.65	1



Makes tie installation easy!

Ty-Rap<sup>®</sup> Installation Tool – Deltec<sup>®</sup> & Stainless Steel

Installs both self-locking Ty-Rap® cable ties and lashing ties

Installs stainless steel ties

WT3D

STD. PKG.	DESCRIPTION	TIE BODY	STD.
Cat. No.		WIDTH IN./MM	PKG. QTY.
WT193A	Cable Tie Installation Tool, 18–50 lbs. (80–222.4N)	.09–.18/2.39–4.67	1

## Easy tension adjustment!

#### Ty-Rap<sup>®</sup> Heavy-Duty Installation Tool — Mil Spec Approved

- Installs Ty-Rap<sup>®</sup> cable ties
- Rugged metallic construction
- Pistol-grip installation tool
- Tensions and cut cable tie tail off flush

STD. PKG. Cat. No.	DESCRIPTION	TIE BODY WIDTH IN./MM	STD. PKG. QTY.
WT199	Installation Tool, 18–50 lbs. (80–222.4N)	.0918/2.39-4.67	1
WT197 * Mil Spec	Installation Tool, 50–120 lbs. (222.4–533.8N) Approved (WT199 — MS90387-1, WT197 —	.18–.30/4.67–7.65 <i>MS90387-2</i> )	1

# ish

STD. PKG. Cat. No.	DESCRIPTION	TIE BODY WIDTH IN./MM	STD. PKG. QTY.
WT3D	Deltec Installation Tool	.1850/4.67-12.70	1
WT3S	Stainless Steel Installation Tool	Up to .50/12.70	1

Thomas®Betts

United States Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services Tel: 888.862.3289

WT3D

WT3S

•

