

## Portable Cord and Cable Fittings

### Metric PG-to-N.P.T. Thread Adapters



Cat. No.	N.P.T. Thread (mating) (in.)	Thread (at housing)
PG11-38	3/8	PG11
PG16-50	1/2	PG16
PG21-75	3/4	PG21
PG29-100	1	PG29
PG29-125	1-1/4	PG29
PG36-125	1-1/4	PG36
PG36-150	1-1/2	PG36



Style may vary depending on size

### Metric Two-Screw Clamp Fittings

Cat. No.	Cable O.D. (in.)		Thread (at housing)
	Min.	Max.	
CC11-38	0.400	0.470	PG11
CC11-38P*	0.250	0.325	PG11
CC135-50	0.400	0.535	PG13.5
CC16-50	0.455	0.625	PG16
CC21-75	0.513	0.815	PG21
CC29-100	0.800	0.175	PG29
CC36-125	1.050	0.450	PG36
CC42-150	1.500	0.800	PG42

\* Plastic



Standard European style

### Metric Cord Grip Fittings

Cat. No.	Cable O.D. (in.)		Thread (at housing)
	Min.	Max.	
CG11-38	0.200	0.470	PG11
CG11-38P*	0.325	0.340	PG11
CG135-50	0.285	0.545	PG13.5
CG16-50	0.285	0.625	PG16
CG21-75	0.395	0.790	PG21
CG29-100	0.780	0.060	PG29
CG36-125	0.960	0.375	PG36
CG42-150	1.630	0.650	PG42

\* Plastic



### Conduit Entry Blind Plug

Cat. No.	Thread (at housing)
CXP722	PG13.5
CXP723	PG16
CXP724	PG21
CXP725	PG29
CXP726	PG36
CXP727	PG42