


Ring Terminals

Nylon-Insulated Large Ring Terminals



Cat. No.	Pkg. Qty.	Wire Range	Max. Ins. (in.)	Bolt Hole	Rec. Tool	Dimensions (in.)				Stock Thick. (in.)
						A	B	C	M	
Flex Class 41/24										
RD167	200	8	0.340	#8	ERG4007	1.48	0.42	0.28	1.29	0.04
RD8-10	25			#10		1.48	0.42	0.28	1.29	
RD367	200			#10		1.48	0.42	0.28	1.29	
RD8-14	25			1/4 in.		1.54	0.46	0.36	1.32	
RD717	200			1/4 in.		1.54	0.46	0.36	1.32	
RD8-516	25			5/16 in.		1.63	0.57	0.36	1.35	
RD727	200			5/16 in.		1.63	0.57	0.36	1.35	
RD8-38	25			3/8 in.		1.63	0.57	0.36	1.35	
RD737	200			3/8 in.		1.63	0.57	0.36	1.35	
RD8-12*	25		0.310	1/2 in.	TBM6S	1.79	0.82	0.55	1.39	
RD757*	200			1/2 in.		1.79	0.82	0.55	1.39	
RD10161	200	8AN	0.270	#8	ERG4007	1.40	0.41	0.24	1.20	0.04
RD10361	200			#10		1.40	0.41	0.24	1.20	
RD10711	200			1/4 in.		1.45	0.45	0.27	1.22	
RD10721	200			5/16 in.		1.53	0.56	0.34	1.25	
RD10731	200			3/8 in.		1.53	0.56	0.34	1.25	
Flex Class 63/24										
RE6-10	20	6	0.420	#10	ERG4007	1.65	0.49	0.28	1.40	0.04
RE267	200			#10		1.65	0.49	0.28	1.40	
RE6-14	20			1/4 in.		1.65	0.49	0.28	1.40	
RE717	200			1/4 in.		1.65	0.49	0.28	1.40	
RE6-516	20			5/16 in.		1.76	0.61	0.34	1.47	
RE727	200			5/16 in.		1.76	0.61	0.34	1.47	
RE6-38	20			3/8 in.		1.76	0.61	0.34	1.47	
RE737	200			3/8 in.		1.76	0.61	0.34	1.47	
RE6-12*	20		0.395	1/2 in.	TBM6S	1.83	0.82	0.55	1.43	
RE757*	200			1/2 in.		1.83	0.82	0.55	1.43	
RE10261	200	6AN	0.315	#10	ERG4007	1.55	0.49	0.24	1.31	0.04
RE10711	200			1/4 in.		1.55	0.49	0.27	1.31	
RE10721	200			5/16 in.		1.70	0.60	0.34	1.40	
RE10731	200			3/8 in.		1.70	0.60	0.34	1.40	
Flex Class 105/24										
RF4-10	15	4	0.510	#10	TBM6S	1.76	0.56	0.36	1.49	0.04
RF267	100			#10		1.76	0.56	0.36	1.49	
RF4-14	15			1/4 in.		1.76	0.56	0.36	1.49	
RF717	100			1/4 in.		1.76	0.56	0.36	1.49	
RF4-516	15			5/16 in.		1.84	0.62	0.35	1.53	
RF727	100			5/16 in.		1.84	0.62	0.35	1.53	
RF4-38	15			3/8 in.		1.84	0.62	0.35	1.53	
RF737	100			3/8 in.		1.84	0.62	0.35	1.53	
RF757*	100		0.500	1/2 in.	TBM6S	1.90	0.82	0.55	1.49	
RF10261	100			#10		1.78	0.55	0.30	1.51	
RF10711	100	4AN	0.380	1/4 in.	ERG4007	1.78	0.55	0.30	1.51	0.04
RF10721	100			5/16 in.		1.80	0.62	0.34	1.49	
RF10731	100			3/8 in.		1.80	0.82	0.34	1.49	

*Brazed Seam
AN=Aircraft Wire

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins. (in.)	Bolt Hole	Rec. Tool	Dimensions (in.)				Stock Thick. (in.)
						A	B	C	M	
RG2-10										
RG267	50	2	0.588	#10	TBM6S	2.15	0.69	0.40	1.83	0.05
RG2-14	10			1/4 in.		2.15	0.69	0.40	1.83	
RG717	50			1/4 in.		2.15	0.69	0.40	1.83	
RG2-516	10			5/16 in.		2.15	0.69	0.40	1.83	
RG727	50			5/16 in.		2.15	0.69	0.40	1.83	
RG2-38	10			38 in.		2.15	0.69	0.40	1.83	
RG737	50			38 in.		2.15	0.69	0.40	1.83	
RG2-12	10			1/2 in.		2.35	0.80	0.49	1.93	
RG757	50			1/2 in.		2.35	0.80	0.49	1.93	
RG9711	50			14 in.		2.07	0.69	0.40	1.74	
RG9731	50	1/0	0.629	38 in.	TBM6S	2.07	0.69	0.40	1.74	0.06
RG9751	50			1/2 in.		2.26	0.80	0.49	1.84	
RH717	50			14 in.		2.14	0.77	0.43	1.81	
RH727	50			5/16 in.		2.14	0.77	0.43	1.81	
RH737	50			38 in.		2.14	0.77	0.43	1.81	
RH757	50			1/2 in.		2.34	0.77	0.54	1.90	
RH9711	50	1AN	0.500	1/4 in.	TBM6S	2.14	0.77	0.44	1.81	0.06
RH9731	50			38 in.		2.14	0.77	0.44	1.81	
RH9751	50			1/2 in.		2.34	0.77	0.54	1.90	
RJ717	100			1/4 in.		2.34	0.83	0.46	1.96	
RJ727	100			5/16 in.		2.34	0.83	0.46	1.96	
RJ737	100			38 in.		2.34	0.83	0.46	1.96	
RJ757	100	2/0	0.675	1/2 in.	TBM6S	2.48	0.89	0.54	2.03	0.07
RJ9711	50			14 in.		2.35	0.83	0.46	1.97	
RJ9731	50			38 in.		2.35	0.83	0.46	1.97	
RJ9751	50			1/2 in.		2.49	0.89	0.55	2.04	
RK717	25			14 in.		2.60	0.93	0.54	2.21	
RK727	25			5/16 in.		2.60	0.93	0.54	2.21	
RK737	25	3/0	0.765	38 in.	TBM6S	2.60	0.93	0.54	2.21	0.07
RK9731	100			38 in.		2.52	0.93	0.55	2.14	
RK9751	100			1/2 in.		2.60	0.93	0.55	2.15	
RL737	25			38 in.		2.83	1.04	0.57	2.35	
RL757	25			1/2 in.		2.83	1.04	0.57	2.35	
RL9731	25			38 in.		2.83	1.04	0.57	2.36	
RL9751	25	4/0AN	0.680	12 in.	TBM6S	2.83	1.04	0.57	2.36	0.07
RM737	20			38 in.		3.00	1.13	0.65	2.51	
RM747	20			7/16 in.		3.00	1.13	0.65	2.51	
RM757	20			12 in.		3.00	1.13	0.65	2.51	
RM9731	20			38 in.		3.00	1.13	0.66	2.51	
RM9751	20			1/2 in.		3.00	1.13	0.66	2.51	