

Cable Strippers, Cutters and Other Tools

Li Cutter for steel, ACSR, Al, Cu



- Designed for one-handed control of blade advancement and retraction
- Rotating head to allow maximum flexibility for cutting
- Features a two-stage rapid advance ram for reduced cycles with overload bypass protection, which will pop off if the material is beyond the cutter's capacity
- Cuts up to 1-1/2 in. O.D. Copper, Aluminum and ACSR cable
- Cuts rebar, ground rod up to 5/8 in. and wire rope up to 3/4 in.
- 14.4 V DC

Specifications

- Capacity: wire rope 3/4 in., Rebar 5/8 in., Ground Rod 5/8 in. ACSR 1-1/2 in., Cu/Al cable 1-1/2
- Dimensions (L x W x H): 17.5 in. x 2.5 in. x 13 in.
- Battery: 14.4 VDC
- Weight with Battery: 14.6 lb.

Cat. No.	Description	Pkg. Qty.
TBM58PCTS-LI	Li cutter for steel, ACSR, Al, Cu	1

297-32136 Hydraulic Cutting Head

- Heavy-duty cutter with high strength steel blades
- Cuts both aluminum and copper wire to 1-1/2 O.D.
- Cutter supplied with carrying case

Specifications

- Max. Cutting Capacity (aluminum and copper): 1-1/2 in. O.D.
- Dimensions (L x W x H): 14-1/2 x 2-1/2 in. x 4 in.
- Weight: 8.5 lb.

Contact Tool Service for replacement blades.



Cat. No.	Description	Pkg. Qty.
297-32136	Hydraulic Cutting Head	1

TBM40HCRH Hydraulic Cutting Head

- Heat-treated, high-strength steel blades for clean cuts and long service life
- Quick automatic coupler speeds connection to hydraulic systems
- Cutter supplied with carrying case

Specifications

- Max. Cutting Capacity (copper, aluminum and telecommunications cable): Up to 3.35 in. O.D.*
- Hydraulic Operating Pressure: 10,000 psi (maximum)
- Dimensions (L x W): 15.94 in. x 5.63 in.
- Weight: 10.8 lb.

* Not designed for cutting steel-reinforced conductors



Contact Tool Service for replacement blades.

Cat. No.	Description	Pkg. Qty.
TBM40HCRH	Hydraulic Cutting Head	1