

Fastening Products

Cable Tie Mounting Bases



Natural nylon colour. Temperature Rating: 0°C to 66°C (32°F to 150°F). *Synthetic Rubber Adhesive.

Great for securing cables!


- Provides a fast and convenient method of securing bundles
- Single-piece design offers reduced installation time and maximized inventory control
- Integral top cover incorporates a unique ratchet design that is fully adjustable and releasable
- Available in a pressure-sensitive adhesive or screw mount design

		-	Maximum		Clampir	ng Area		Std. Pkg.	
Std. Pkg. Cat. No.	Bulk Pkg. Cat. No.	Base Style	Height (in.)	Min. (in.)	Min. (mm)	Max. (in.)	Max. (mm)		Bulk Pkg.
One-Piece Mo	ounting Clamp								
TC5349A-TB	TC349A-TB	SRA* Adhesive	0.57	0.18 x 0.24	4.57 x 6.10	0.35 x 0.24	0.89 x 6.10	100	1,000
TC5350A-TB	TC350A-TB	SRA Autresive	0.89	0.20 x 0.59	5.08 x 14.99	0.45 x 0.59	11.43 x 14.99		

Great for securing cables!

Temperature Rating: 0°C to 66°C (32°F to 150°F). *650-41349 has two holes for mounting.





		Max. Tie Width Accom.	Max. Tie Length		Width			
Cat. No.	Mounting Method		(in.)	(mm)	(in.)	(mm)	Material	Pkg.
Aluminum Mounti	ng Plates							
TC105	TC2PA/Screws		1.00	25.40	0.50	12.70	Aluminum	1,000
TC824-TB	TC2PA	0.19	1.38	34.93	0.38	9.65		
650-41349*	TC2PA/Screws							



Super strong adhesive!

Cat. No.	Mounting Method					
Mounting Base Ad	hesive					
TC2PA	Consists of one tube each, adhesive and activator	1				



