



Fittings and Brackets

Flat Fittings


AB206
 AB206HDGC
 AB206EG
 AB206
 AB206SS6C
 Wt./C 35 lb.




AB207
 AB207HDGC
 AB207EG
 AB207
 AB207SS6C
 Wt./C 52 lb.




X207
 X207HDG
 X207EG
 X207
 X207SS6
 Wt./C 78 lb.




X208
 X208HDG
 X208EG
 X208
 X208SS6C
 Wt./C 88 lb.




AB219
 AB219HDGC
 AB219EG
 AB219
 AB219SS6C
 Wt./C 53 lb.



AB220
 AB220HDGC
 AB220EG
 AB220
 AB220SS6C
 Wt./C 78 lb.




AB240
 AB240HDG
 AB240EG
 AB240
 Wt./C 69 lb.




AB241

Cat. No.	Bolt Size (in.)	Wt./C lb.
AB241-1/4*	1/4	18
AB241-5/16*	5/16	18
AB241-3/8*	3/8	18
AB241-1/2*	1/2	17
AB241-5/8*	5/8	15
AB241-3/4*	3/4	14

*Finishes
 • HDGC • GoldGalv®
 • EG • SS6C




AB242
 AB242HDGC
 AB242EG
 AB242
 Wt./C 9 lb.




For use with either 3/8 in. or 1/2 in. hanger rod.


AB253
 AB253HDGC
 AB253EG
 AB253
 AB253SS6C
 Wt./C 97 lb.




AB255
 AB255HDGC
 AB255EG
 AB255
 Wt./C 70 lb.




AB257
 AB257HDGC
 AB257EG
 AB257
 Wt./C 105 lb.




AB261
 AB261HDGC
 AB261EG
 AB261
 Wt./C 148 lb.



AB263
 AB263HDGC
 AB263EG
 AB263
 AB263SS6
 Wt./C 150 lb.



AB265
 AB265HDGC
 AB265EG
 AB265
 Wt./C 105 lb.




Standard Dimensions	Value
Hole Spacing	→ 13/16 in. From End
Hole Spacing	→ 1-7/8 in. Centers
Hole Size	→ 9/16 in. Diam.
Material	→ 1-5/8 in. Width
Material	→ 1/4 in. Thick

Materials	Value
HDG(C)	→ Hot-Dipped Galvanized
EG(C)	→ ElectroGalvanized
(No suffix)	→ GoldGalv®
SS6(C)	→ Stainless Steel 316


Fittings and Brackets

90° Fittings


AB201
 AB201HDGC
 AB201EG
 AB201
 AB201SS6C
 Wt./C 35 lb.




AB202
 AB202HDGC
 AB202EG
 AB202
 AB202SS6C
 Wt./C 35 lb.




AB203
 AB203HDGC
 AB203EG
 AB203
 AB203SS6C
 Wt./C 58 lb.




AB204
 AB204HDGC
 AB204EG
 AB204
 AB204SS6C
 Wt./C 58 lb.




AB205
 AB205HDGC
 AB205EG
 AB205
 AB205SS6C
 Wt./C 78 lb.




AB213
 AB213HDGC
 AB213EG
 AB213
 Wt./C 125 lb.



AB214
 AB214HDGC
 AB214EG
 AB214
 AB214SS6C
 Wt./C 125 lb.




AB216
 AB216HDGC
 AB216EG
 AB216SS6C
 Wt./C 135 lb.




AB252

Cat. No.	A (in.)	Wt./C lb.
AB252-1*	3-7/8	61
AB252-2*	5-7/8	84
AB252-3*	7-7/8	107
AB252-4*	9-7/8	130


*Finishes
 • HDGC • EG • GoldGalv®




AB254R
 AB254RHDGC
 AB254REG
 AB254R
 Wt./C 105 lb.




AB254L
 AB254LHDGC
 AB254LEG
 AB254L
 Wt./C 105 lb.




AB260R
 AB260RHDGC
 AB260REG
 AB260R
 Wt./C 58 lb.




AB260L
 AB260LHDGC
 AB260LEG
 AB260L
 Wt./C 58 lb.



AB274
 AB274HDG
 AB274EG
 AB274
 Wt./C 70 lb.



AB275
 AB275HDGC
 AB275EG
 AB275SS6C
 Wt./C 77 lb.



Standard Dimensions	Value
Hole Spacing	→ 13/16 in. From End
Hole Spacing	→ 1-7/8 in. Centers
Hole Size	→ 9/16 in. Diam.
Material	→ 1-5/8 in. Width
Material	→ 1/4 in. Thick

Materials	Value
HDG(C)	→ Hot-Dipped Galvanized
EG(C)	→ ElectroGalvanized
(No suffix)	→ GoldGalv®
SS6(C)	→ Stainless Steel 316