Beam Clamps



Design Loads

Where design loads are indicated, they provide for a safety factor of 3 in conformance with the American Standard Code for Pressure Piping. For more information, see page A57 for Engineering Data and Specifications.

Finishes and Special Materials

Hot-Dipped Galvanized (HDGC) is standard for all Superstrut® beam clamps. The material is zinc coated after fabrication providing total product protection on all surfaces. The fabricated beam clamps are suspended and then dipped into tanks of hot zinc for a prolonged period, creating a coherent bond.


Selected beam clamps can also be available in GoldGalv® (no suffix) or Stainless Steel Type 316 (SS6C). Contact your Regional Sales Office for availability and minimum quantities.



Surface Raceway and Lighting Systems

Fixture Fittings


802 **Raceway Joiner With Reinforcing Plate**



Furnished complete with nuts.

Cat. No.	For Channel	Wt./C lb.
A802EG	A Series	158
B802EG	B Series	112
E802EG	E Series	170
H802	H Series	182

805 **End Cap With Knockout**



21

31

machine screw and AB100-1/4 nut. **For Channel** Wt./C lb. Cat. No. **A805EG** A Series


H805EG

A853L		
Channel	Hanger -	Long



Long type for all Series channel. Wt./C 48 lb.


Raceway Joiner & Seal



Furnished complete with 1/4 in. x 5/8 in. machine screws and AB100-1/4 nuts.

Cat. No.	A (in.)	For Channel	Wt./C lb.
A822	1-11/16	A Series	75
B822	7/8	B Series	56

A213 Inside Joiner



For A1200 Series channel. Only available in GoldGalv® finish.

809 **Tapped End Cap**



Rod Size	For Channel	Wt./C lb.		
A809-3/4EG	A Series	2		
E809-3/4EG	E Series	26		

A853 **Channel Hanger**



Use hanger rod 3/8 in. or 1/2 in. Use with A, AR, B, BR or C Series single channel. Wt./C 25 lb.

A854 **Channel Hanger**




Illustration showing A854 with nut and bolt furnished to attach to fluorescent fixture. Use with A. B. C or D Series channel. Wt./C 34 lb.

A854L **Channel Hanger - Long**



Illustration showing A854L with nut and bolt furnished to attach to fluorescent fixture. Use with E and H Series channel as well as A, B, C or D Series channel. Wt./C 51 lb.