D Series 10 A 600 VAC

7 or 8, 15, 25 & 40 Contacts + Ground

Accessories

Wiring Adapter Insert for use with Panel Bases; allows single access direction panel-build wiring and easy terminal ID for service and testing

Cat. No.	Description	
WAM-1	Label Insert Clip	
WAM1B	Strip Blank	
WAM1N64	Strip Nos. 1–64	
WAM1AZ	Strip Letters A–Z	



Crimp Tool	
Cat. No.	
WT80	



Extraction Tool
Cat. No.
RT614

See page D54 for POF installation and tools info.

Install to Matching Series Hood/Base

15	25	40
100000	13:20:20-	Allitone,
4 13	9	9
	15	15 25

Crimp Terminal Inserts

Crimp Terminal Inserts	7 or 8 + G	15 + G	25 + G	40 + G
Male Insert (Order contacts below)	MC407D or MC408D	MC415D	MC425D	MC440D
Female Insert (Order contacts below)	FC307D or FC308D	FC315D	FC325D	FC340D

Contacts Sold Separately

Screw Terminal Wiring Adapter Blocks

Screw Termin	al Wiring Adapter Blocks	_	_	_	40 + G
	Male Insert, Ground L. 26–16 AWG (0.2–1.5mm²)	_	_	_	MS440WAL
	Female Insert, Ground L. 26–16 AWG (0.2–1.5mm²)	_	_	_	FS340WAL

Contacts Selection Chart

Crimp Contacts	Wire AWG (mm²)	Identification
	22+ AWG (0.1437)	1
↑ I.D.	20 AWG 0 (0.5)	2
▼ 1	18 AWG (0.75–1)	3
	16 AWG (01.5)	4
	14 AWG (2.5)	5

For Optic Contacts

Crimp Contacts	Wire AWG (mm²)	Identification
	18 AWG (0.75–1)	3

For All Crimp Terminal "D" Inserts:

Female	Male
FP22SD	MP22SD
FP20SD	MP20SD
FP18SD	MP18SD
FP16SD	MP16SD
FP14SD	MP14SD

Female	Male
FP18SD	MP18SD

