

# NEER Connectors for Nonmetallic Sheathed Cable

## RX: Two Piece Nonmetallic Sheathed Cable Two Screw Connector

### Applications


- To terminate one or more nonmetallic sheathed cables to a knockout in a dry location box or enclosure.
- Used in “old work” locations.

### Standard Material/Finish

- Steel/zinc plated



RX-50



Trade Size (Inches) EMT to Flex.	Catalog Number	Dimensions in Inches/Millimeters	
		A	B
1/2	<b>RX-50</b>	1.33/ 33.8	0.64/ 16.3
3/4 or 1	<b>RX-75</b>	1.75/ 44.5	0.76/ 19.3
1-1/4	<b>RX-125</b>	2.25/ 57.2	0.85/ 21.6
1-1/2 or 2	<b>RX-150</b>	2.73/ 69.3	0.84/ 21.3

## NST: Snap-Tite Plastic Nonmetallic Sheathed Cable Connector

### Applications

- These PVC connectors are used to terminate nonmetallic sheathed cable to 1/2” knockout in a dry location box or enclosure.

### Standard Material

- PVC

### Certifications and Compliances


- UL Standard: 514B
- UL Listed: E25015
- NEMA: FB-1

### Note:

- NST-50 is listed for use with one 14-2, 14-3, 12-2, 12-3, 10-2 or 10-3 nonmetallic sheathed cable or two 14-2, 14-3 or 12-2 nonmetallic sheathed cables.



NST-50



Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		
		A	B	C
1/2	<b>NST-50</b>	1.37/ 34.8	0.48/ 12.2	1.00/ 25.4