

NEER Nylon NMM Straight and 90° and Liquidtight Connectors

For Type B Nonmetallic Conduit.

Applications

- Terminate and seal liquidtight flexible Type B nonmetallic conduit, to either oiltight, liquidtight, or raintight box or enclosure.
- Connectors can be used with tapered thread female entry or unthreaded knockout.

Features

- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents.
- No disassembly required; push the conduit or tubing onto the ferrule, then tighten the domed sealing nut.
- Connectors are reusable.
- Furnished with locknut and sealing ring.
- Suitable for wet locations.
- Liquidtight/raintight/oiltight.

Standard Material

- Nylon: gray

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E302405
- NEMA: FB-1



NMM-01

Applications

- Terminate and seal liquidtight flexible Type B nonmetallic conduit at a 90° angle, to either oiltight, liquidtight or raintight box or enclosure.
- Connectors can be used with tapered thread female entry or unthreaded knockout.

Features

- Furnished with locknut and sealing ring.
- Suitable for wet locations.
- Liquidtight/raintight/oiltight.

Standard Material


- Nylon: gray

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E302405
- NEMA: FB-1



NML-01



Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		
		Body Length	Thread Length	Diameter
3/8 (1/2 knockout)	NMM-01	2.14/54.4	0.62/15.7	1.42/36.1
1/2	NMM-11	2.13/54.1	0.63/16.0	1.42/36.1
3/4	NMM-21	2.25/57.2	0.63/16.0	1.66/42.2
1	NMM-31	2.52/64.0	0.78/19.8	1.93/49.0

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		
		A	B	C
3/8 (1/2 knockout)	NML-01	2.00/50.8	0.50/12.7	3.06/77.7
1/2	NML-11	2.07/52.6	0.51/13.0	3.19/81.0
3/4	NML-21	2.28/57.9	0.51/13.0	3.40/86.4
1	NML-31	2.90/73.7	0.77/19.6	3.40/86.4