

Large-Size Nylon Flexible Conduits and Connectors

GH Tube Clamps

- For mounting conduits in a wide range of applications
- High-grade, specially formulated polyamide 6
- One-piece design
- Integrated rib provides axial strain relief
- Allows turning of the conduit, thus avoiding torsion stresses
- Pre-fixation on the conduit possible
- Allows solid fixation with two screws
- Self extinguishing
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles
- No corrosion



Temperature range: -40° C to 105° C

CAT. NO. BLACK	CAT. NO. GRAY	FITS TO CONDUIT SIZE		DIMENSIONS WIDTH	FIXING SCREW
		NW	METRIC		
BGH-56	SGH-56	56	63	26.0mm	(2) M8
BGH-70	SGH-70	70	80	30.0mm	(2) M8
BGH-95	SGH-95	95	106	30.0mm	(2) M8

SGS Tube Clamps

- For mounting of static conduits
- Galvanized steel
- Elastomer profile (EPDM)
- Elastomer profile, free from halogens
- Smooth connection to PMAFLEX[®] corrugated conduits
- Good ozone and aging resistance



Temperature range: -50° C to 105° C

CAT. NO. BLACK	FITS TO NW	DIMENSIONS		
		WIDTH	HEIGHT	DEPTH
SGS-36	36	80.0mm	48.0mm	19.0mm
SGS-48	48	94.0mm	58.0mm	19.0mm
SGS-56	56	118.0mm	72.0mm	24.0mm
SGS-70	70	130.0mm	85.0mm	24.0mm
SGS-95	95	156.0mm	110.0mm	24.0mm
SGS-125	125	200.0mm	152.0mm	24.0mm

SG03 Conduit Seal Rings

- Used at the conduit end for sealing between the PMAGRIP flanges GG/GI/GO and PMAFLEX[®] Jumbo conduits
- Nitrile rubber

CAT. NO. BLACK	FITS TO NW	INSIDE DIAMETER	OUTSIDE DIAMETER	DIMENSIONS WIDTH
SG03-56	56	49.5mm	61.0mm	1.5mm
SG03-70	70	61.5mm	74.0mm	1.5mm
SG03-95	95	86.0mm	102.0mm	1.5mm
SG03-125	125	122.0mm	142.0mm	2.0mm



Temperature range: -40° C to 105° C